

Product Data Sheet



MEDAL TEXTURE ACRYLIC

No	MP02
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Medal Texture Coat is a flexible exterior wall coating, which is recommended for use on exterior concrete and cement-plastered surfaces. This product contains Mica for stretch and Granite for strength. It covers all hairline cracks, and it has excellent alkali and water-resistant properties. Also suitable on areas where a fine durable mat textured finish is required.

PRODUCT USES:

- New or previously painted surfaces made from Cement Plaster; Concrete; Brickwork & Gypsum Plaster.
- Asbestos/Fibre Cement Boards.
- Primed Metal Surfaces.
- Ideal for Exterior Walls.

PRODUCT BENEFIT:

- Hides Hairline Cracks
- Excellent UV Resistance
- Ideal for Exterior Surfaces
- 5 Year Guarantee

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of Medal Plaster Primer, followed by two coats of Medal Texture Coat.

Asbestos/Fibre Cement: Apply one coat of Medal Plaster Primer, followed by two coats of Medal Texture Coat.

Iron & Steel: Apply one coat of Medal Dual Steel Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Texture Coat.

Timber/Wood: Sand surface to a smooth finish. Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Texture Coat.

Gypsum Plaster (Rhinolite/Rhinoglide): Apply one coat of Medal Plaster Primer, followed by two coats of Medal Texture Coat.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Medal Plaster bond prior to applying two coats of Medal Texture Coat.

APPLICATION:

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or lambs wool paint roller, and allow +/- 4 hours drying time between coats. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in white, standard colours and three tintbases.

SPREADING RATE

This product will cover approximately 5-7m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic Pva
Finish	Matt
Drying Time @ 25°C	Touch Dry: 30 Min. Hard Dry: 4 Hrs.
Re-coating Time	4 Hours
Viscosity	125-136 Krebs
Units	
Specific Gravity	1.38 kg / litre
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS:

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST:

Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

QUALITY GUARANTEE:

Medal Paints will guarantee this product for a period of five years subject to the adherence by the purchaser to comply with the "Instructions for Use" appearing on the reverse side of each can. Refer to the back of pack for more details.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

