

Product Data Sheet



Premium Cover All

No	MP01
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Premium Cover All is luxury paint with a durable suede sheen finish, which has been specifically designed to protect and decorate all exterior walls. This product is fully washable combined with excellent dirt/stain and UV resistance properties. It can be applied to numerous surfaces such as Cement Plastered Walls, Asbestos or Fibre Cement and on other areas where a suede sheen finish is required.

PRODUCT RECOMMENDED USES

- New and previously painted surfaces made from Cement Plaster, Concrete, Brickwork & Gypsum Plaster.
- Asbestos/Fibre Cement Fascias & Ceiling Boards.
Ideal for Exterior Walls.

PRODUCT BENEFITS

- Pure acrylic paint
- Stain & dirt resistant
- Fully washable
- Soft touch finish
- Apply with Brush or Roller
- Guaranteed for 10 years

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of Medal Plaster Primer followed by two coats of Medal Premium Cover All.

Asbestos/Fibre Cement: Apply one coat of Medal Plaster Primer followed by two coats of Medal Premium Cover All.

Gypsum Plaster (Rhinolite): Apply one coat of Medal Plaster Primer followed by two coats of Medal Premium Cover All.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Medal Plasterbond, prior to applying two coats of Medal Premium Cover All. Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one coat of Medal Universal Undercoat, followed by two coats of Medal Premium Cover All.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furpile / lambswool) paint roller, and allow +/- 4 hours drying time between coats. Clean tools (brushes & rollers) with water immediately after use.

COLOUR RANGE

Available in white, standard colours and three different tint bases.

SPREADING RATE

Approximately 8-10 m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Pure Acrylic
Finish	Suede Sheen
Drying Time @ 25°C	Touch Dry: 30 Min Hard Dry: 4 Hours

Re-coating Time	4 Hours
Viscosity	108-120 Krebs Units
Specific Gravity	1.42 kg / litre
Washability	>10.000 Scrubs
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C
- Keep out of reach of children
- Wash hands with Water immediately after use
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

GUARANTEE

Medal Paints will guarantee this product for a period of ten years subject to the adherence by the purchaser to comply with the "Instructions for Use "appearing on the reverse side of each can. Refer back of pack for more details.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

