

PRODUCT DATA SHEET

MEDAL DUAL STEEL PRIMER (Steel & Galvanised Iron)	No	MPP05
	Date	04/11

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Dual Steel Primer is a water-based metal primer, which is specifically designed to protect all ferrous metal surfaces such as Mild Steel and Galvanised Iron. This product has excellent adhesion and "rust inhibiting" properties.

PRODUCT USES

- Surfaces made from Mild Steel such as Door & Window Frames; Burglar Bars; Carports & Garage Doors etc.
- Galvanised Iron surfaces such as Roofs, Gutters and Downpipes etc.

PRODUCT BENEFITS

- Dual-Purpose Primer
- Quick Drying (Water-Based)
- Excellent Adhesion Properties
- A Sound Surface for Top Coats
- Apply with a Brush or Roller
- Quality Guaranteed

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before commencing work.

Mild Steel: Remove grease and surface rust with a wire brush or sandpaper. Apply one coat of Medal Dual Steel Primer; prior to applying two topcoats of paint in the desired finish.

Galvanised Iron: Clean surface with Medal Galvanised Iron Cleaner, and allow surface to dry before commencing to paint. Apply one coat of Medal Dual Steel Primer; prior to applying two topcoats of paint in the desired finish.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. Apply this product with a paintbrush or (short nap) paint roller, and allow +/- 4 hours drying time before applying the final coat/s of paint. Clean tools (paintbrushes & rollers) with Water immediately after use.

COLOUR RANGE

Red.

SPREADING RATE

This product will cover approximately 8-10m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

Type	Acrylic
Finish	Matt
Drying Time @ 25°C	Touch Dry : 30 Minutes Hard Dry : 4 Hours
F.O.G.	20-30 µ
Viscosity	95 - 108 Krebs Units
Storage	Dry and Cool
Pack Size	1Lt; 5Lt; 20Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Mineral Turpentine; Crackfiller; Paint Scraper; Stepladder.

QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

For more information, please contact our Customer Service Centre on 08600 Medal (08600-63325) where we will gladly assist you with any queries you may have. This product is proudly manufactured by Medal Paints (Pty) Ltd. (Est. 1978) Cnr Main Reef & Kelvin Roads, Industria, Johannesburg Tel: (011) 661-5700.