

PRODUCT DATA SHEET

EVERBOND WATERPROOFING

No	EW01
Date	04/11

Everbond waterproofing products are developed and marketed by Medal Paints to meet the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Everbond is a non-toxic, fibre-reinforced flexible pure acrylic waterproofing system used in a wide variety of applications. It has extremely high UV resistance and excellent elongation properties, and it can take submersion under water for long periods of time. It can be applied to different surfaces to provide complete protection against the harshest weathering elements.

PRODUCT USES

- Sealing Concrete Dams, Reservoirs and Fishponds.
- Waterproofing Roofs, Walls and Parapet Walls.
- Protects Timber or Steel against Corrosion.
- Salt Mist protection.

PRODUCT BENEFITS

- Non-Toxic (water-based)
- Membrane-Free System.
- Excellent UV Resistance
- Over-Coat with Water-Based Paints
- Apply with Brush, Roller or Spray
- Quality Guaranteed

PREPARATION FOR DIFFERENT SURFACES

For more specific information related to correct application methods used for the different substrates, please refer to the relevant data specification sheets as described hereunder:

- SP01: Asbestos Roofs**
- SP02: Balconies**
- SP03: Concrete Roofs**
- SP04: Damp Substrates**
- SP05: Expansion Joints**
- SP06: Gutters**
- SP07: IBR & Corrugated Roofs**
- SP08: Parapet Walls & Hairline Cracks**
- SP09: Showers**
- SP10: Tiled Roofs**
- SP11: Water Retainers**

The above-mentioned data specification sheets are available on request from Medal Paints.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush, paint roller or spray, and allow 2 to 6 hours drying time between coats. Clean tools (paintbrushes/equipment) with Water immediately after use.

COLOUR RANGE

Available in grey and standard colours.

SPREADING RATE

This product will cover approximately 1 litre /m², depending on film thickness applied. Based on SABS test method.

TECHNICAL DATA

Type	Pure Acrylic
Finish	Semi-Sheen
Viscosity – Krebs Units	120 – 125 Kus
Drying Time @ 25°C	Touch Dry: 30 Min to 1 Hour Hard Dry :24- 48- Hours
Re-coating Time	4 – 6 Hours
Tensile Strength	2 Mpa
Flexibility	100%
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt; 20Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.
- This product is not suitable for Swimming Pools.

GUARANTEE

This product is marketed by Medal Paints under the Everbond brand name, which is guaranteed for a period of up to five years and subject to: 1. The affected surface/s are maintained every 2 years with one coat of Everbond and 2. The "Instructions for Use" listed under the relevant Data Specification sheets have been correctly followed by the end user.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

For more information, please contact our Customer Service Centre on 08600 Medal (08600-63325) where we will gladly assist you with any queries you may have. This product is proudly manufactured by Medal Paints (Pty) Ltd. (Est. 1978) Cnr Main Reef & Kelvin Roads, Industria, Johannesburg Tel: (011) 661-5700.

04/2011