

PRODUCT DATA SHEET

**MEDAL
MASONRY PRIMER**

No	MPP03
Date	04/11

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Masonry Primer is a versatile product, which is primarily used as a prime-coat for new concrete and cement-plastered surfaces. This product contains Pliolite combined with excellent adhesion, hiding power and alkali-resistant properties.

PRODUCT USES

- Suitable for Interior and Exterior surfaces made from Cement Plaster, Concrete, and Gypsum Plaster.

PRODUCT BENEFITS

- Good Alkali Resistance
- Excellent Hiding Power
- Apply with Brush or Roller
- Interior & Exterior Use
- Quality Guaranteed

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition, and free from loose particles of dust/cement prior to painting.

Concrete/Cement Plaster: Apply one coat of Medal Masonry Primer, followed by two topcoats of paint in the desired finish.

Asbestos/Fibre Cement: Apply one coat of Medal Masonry Primer, followed by two topcoats of paint in the desired finish.

Gypsum Plaster: Apply one coat of Medal Masonry Primer thinned by 20-30% with Mineral Turpentine to aid penetration. Apply two topcoats of paint in the desired finish.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. If thinning is required use Mineral Turpentine. Apply this product with a paintbrush or (Mohair) paint roller, and allow overnight drying time before applying the final coat/s of paint. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use.

COLOUR RANGE

White.

SPREADING RATE

This product will cover approximately 6-8m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

Type	Solvent-Based
Finish	Matt
Drying Time @ 25°C	Touch Dry : 40 Minutes Hard Dry : 16 Hours
Re-coating Time	16 Hours
F.O.G.	20-25 μ
Viscosity	85-95 Krebs Units
Specific Gravity	1.3 kg / litre
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of lower than 35°C.
- Keep out of reach of children.
- Wash hands with Mineral Turpentine immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Mineral Turpentine; Crackfiller; Paint Scraper; Stepladder.

QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

For more information, please contact our Customer Service Centre on 08600 Medal (08600-63325) where we will gladly assist you with any queries you may have. This product is proudly manufactured by Medal Paints (Pty) Ltd. (Est. 1978) Cnr Main Reef & Kelvin Roads, Industria, Johannesburg Tel: (011) 661-5700.

04/2011