

# Product Data Sheet



## PROFESSIONAL TRADE GLOSS ENAMEL

No	MPT8
Date	01/17

Medal Professional Trade products are manufactured to the quality and performance standards to ensure complete customer satisfaction.

### DESCRIPTION

Professional Trade Gloss Enamel is an economy range paint suitable for Interior and Exterior surfaces. A durable product that can be applied to a variety of new or previously painted surfaces such as Cement Plaster; Asbestos/Fibre Cement Wood and Steelwork.

### PRODUCT USES

- New and previously painted surfaces made from Cement Plaster.
- Primed Metal & Wooden Surfaces.
- Ideal for Steel Door & Window Frames; Interior Walls; Kitchen & Bathroom Walls; Gates; Steel Fencing etc.

### PRODUCT BENEFITS

- Glossy Finish
- Fully Washable
- Apply with Brush or Roller
- Interior & Exterior Use
- 5 Year Guarantee

### SURFACE PREPARATION

**New Surfaces:** Surface/s must be thoroughly clean, dry and in sound condition before painting.

**Concrete/Cement Plaster:** Apply one coat of Professional Trade Plaster Primer followed by one coat of Professional Trade Universal Undercoat, and two coats Professional Trade Gloss Enamel.

**Galvanised Iron:** Remove all oil/grease from surface before painting, Apply one coat of Medal Dual Steel Primer, followed by one coat of Professional Trade Universal Undercoat, and two coats Professional Trade Gloss Enamel.

**Iron & Steel:** Remove all grease and surface rust before painting. Apply one coat of Solvent

Etch Primer, followed by one coat of Professional Trade Universal Undercoat, and two coats Professional Trade Gloss Enamel.

**Timber/Wood:** Lightly sand surface to a smooth finish before painting. Apply one coat of Medal Pink Wood Primer followed by one coat of Professional Trade Universal Undercoat, and two coats Professional Trade Gloss Enamel.

**Gypsum Plaster:** Apply one coat of Professional Trade Plaster Primer followed by two coats Professional Trade Gloss Enamel

**Previously Painted Surfaces:** Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Spot prime all bare areas with the correct primer, followed by one coat of Professional Trade Universal Undercoat, and two coats Professional Trade Gloss Enamel.

### APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. If thinning is required use Mineral Turpentine. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (mohair) paint roller, and allow overnight drying time between coats. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use.

### COLOURRANGE

Available in standard colours.

### SPREADING RATE

This product will cover approximately 4 - 6m<sup>2</sup> /litre, depending on surface porosity.

### TECHNICAL DATA

Type	Alkyd
Finish	Gloss
Drying Time @ 25°C	Touch Dry: 40 Minutes Hard Dry : 16 Hours
Re-coating Time	16 Hours
F.O.G.	<10 □
Viscosity	68-72 Krebs units
Specific Gravity	1.10 kg / litre
Storage	Dry and Cool area
Pack Size	1 & 5L

### PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature lower than 35°C.
- Keep out of reach of children.
- Wash hands with Mineral Turpentine immediately after use.
- Skin or Eye contact: clean with fresh water immediately and consult a physician if necessary.

### TOOL CHECKLIST

Paint Brush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Mineral Turpentine; Stepladder.

### QUALITY GUARANTEE

Medal Paints will guarantee this product for a period of five years subject to the adherence by the purchaser to comply with the "Instructions for Use" appearing on the reverse side of each can. Refer to the back of pack for more details.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

