

Product Data Sheet



MEDAL SCHOOL BOARD PAINT

No	MP52
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Medal School Board Paint is an excellent quality water-based paint that has been specially formulated for schools. This product has excellent abrasion resistance for long-term durability.

PRODUCT USES:

- A Long-lasting paint finish for School Boards.

PRODUCT BENEFITS:

- Durable Matt Finish
- Excellent Abrasion Resistance
- Interior Use
- 5 Year Guarantee

SURFACE PREPARATION:

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Cement Plaster, Asbestos/Fibre Cement: Apply one coat of Medal Plaster Primer, followed by two coats of Medal School Board Paint.

Iron & Steel: Apply one coat of Medal Dual Steel Primer, followed by two coats of Medal School Board Paint.

Timber/Wood: Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal School Board Paint.

Previously Painted Surfaces:

Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Sand lightly and apply two coats of Medal School Board Paint. Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one

coat of Medal Universal Undercoat, followed by two coats of Medal School Board Paint.

APPLICATION:

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (short nap) paint roller, and allow overnight drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

COLOURRANGE

Available in Black & Green.

SPREADING RATE

This product will cover approximately 5-7m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

Type	Acrylic
Finish	Matt
Drying Time @ 25°C	Touch Dry: 30 Min. Hard Dry : 4 Hours
Re-coating Time	3 Hours
Viscosity	95 - 105 Krebs units
Specific Gravity	1.30 kg / litre
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crackfiller; Paint Scraper; Stepladder.

QUALITY GUARANTEE:

Medal Paints will guarantee this product for a period of five years subject to the adherence by the purchaser to comply with the "Instructions for Use" appearing on the reverse side of each can. Refer to the back of pack for more details.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

