

Product Data Sheet



MEDAL MID SHEEN ACRYLIC

No	MP04
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Medal Mid-Sheen Acrylic is a superior quality paint with a fine-smooth finish, which has been developed to protect and beautify all interior and exterior surfaces. This product is fully washable with excellent dirt and stain resistance. It can be applied to a variety of surfaces where a durable mid-sheen finish is required.

PRODUCT USES:

- New and previously painted surfaces made from Cement Plaster, Concrete, and Brickwork & Gypsum Plaster.
- Asbestos/Fibre Cement Fascia's & Ceiling Boards.
- Primed Metal & Wooden Surfaces.
- Ideal for Interior & Exterior Walls.

PRODUCT BENEFITS:

- Stain & Dirt Resistant
- Fully Washable
- Good Scrub Resistance
- Excellent Hiding Power
- Interior & Exterior Use
- 7 Year Guarantee

SURFACE PREPARATION:

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of Medal Plaster Primer, followed by two coats of Medal Mid Sheen Acrylic.

Asbestos/Fibre Cement: Apply one coat of Medal Plaster Primer, followed by two coats of Medal Mid Sheen Acrylic.

Iron & Steel: Apply one coat of Medal Dual Steel Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Mid Sheen Acrylic.

Timber/Wood: Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Mid Sheen Acrylic.

Gypsum Plaster (Rhinolite/Rhinoglide): Apply one coat of Medal Plaster Primer, followed by two coats of Medal Mid Sheen Acrylic.

Previously Painted Surfaces:

Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Medal Bonding Liquid, prior to applying two coats of Medal Mid Sheen Acrylic. Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one coat of Medal Universal Undercoat, followed by two coats of Medal Mid Sheen Acrylic.

APPLICATION:

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furpile / lambswool) paint roller, and allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in white and three different types of tint bases.

SPREADING RATE

This product will cover approximately 6-8m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

Type	Acrylic
Finish	Mid-Sheen
Drying Time @ 25°C	
Touch Dry:	30 Min
Hard Dry:	4 Hours
Re-coating Time	4 Hours
Viscosity	95-108 Krebs units
Specific Gravity	1.42 kg / litre
Wash ability	>10.000 Scrubs
Storage area	Dry and Cool
Pack Size	1Lt; 5Lt; 20Lt

PRECAUTIONS:

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST:

Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

QUALITY GUARANTEE:

Medal Paints will guarantee this product for a period of seven years subject to the adherence by the purchaser to comply with the "Instructions for Use" appearing on the reverse side of each can. Refer to the back of pack for more details

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

