

Product Data Sheet



PROFESSIONAL TRADE UNIVERSAL ACRYLIC PVA

No	MPT3
Date	01/17

Medal Professional Trade products are manufactured to the quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Professional Trade Universal Acrylic PVA is a medium quality paint, suitable for all interior and exterior surfaces. This product has excellent hiding power properties. It can be applied to a variety of surfaces where a mat finish is required.

PRODUCT RECOMMENDED USES:

- New and previously painted surfaces made from Cement Plaster, Concrete, Brickwork & Gypsum Plaster.
- Asbestos/Fibre Cement Fascias & Ceiling Boards.
- Primed Metal & Wooden Surfaces.
- Interior & Exterior Walls.

PRODUCT BENEFITS

- Quick Drying
- Good Hiding Power & Whiteness
- Apply with Brush or Lamb wool Roller
- Interior & Exterior Use
- 3 Year Guarantee

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of Professional Trade Plaster Primer, followed by two coats of Professional Trade Universal Acrylic Pva.

Asbestos/Fibre Cement: Apply one coat of Professional Trade Plaster Primer, followed by two coats of Professional Trade Universal Acrylic Pva.

Iron & Steel: Apply one coat of Medal Dual Steel Primer, followed by one coat of Professional Trade Universal Undercoat and

two coats of Professional Trade Universal Acrylic Pva.

Timber/Wood: Apply one coat of Medal Pink Wood Primer, followed by one coat of Professional Trade Universal Undercoat and two coats of Professional Trade Universal Acrylic Pva.

Gypsum Plaster (Rhinolite/Rhinoglide): Apply one coat of Professional Trade Plaster Primer, followed by two coats of Professional Trade Universal Acrylic Pva.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Professional Trade Plasterbond, prior to applying two coats of Professional Trade Universal Acrylic Pva. Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one coat of Professional Trade Universal Undercoat, followed by two coats of Professional Trade Universal Acrylic Pva.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or lamb's wool paint roller, and allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in white and standard colours

SPREADING RATE

This product will cover approximately 6-8m²/litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic Based Pva
Finish	Matt
Drying Time @ 25°C	Touch Dry: 30 Minutes Hard Dry : 4 Hours
Re-coating Time	4 Hours
Viscosity	108-120 Krebs units
Specific Gravity	1.45 kg / litre
Wash ability	+/-700 Scrubs
Storage	Dry and Cool area
Pack Size	5 & 20L

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder

QUALITY GUARANTEE:

Medal Paints will guarantee this product for a period of three years subject to the adherence by the purchaser to comply with the "Instructions for Use" appearing on the reverse side of each can. Refer to the back of pack for more details.

