

Product Data Sheet



Premium Velvet Silk

No	MP03
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Premium Velvet Silk is a luxury paint with a velvet-sheen finish, which has been especially developed to provide complete protection to all interior surfaces. This product is fully washable and has excellent dirt and stain resistant properties. It can be applied to numerous surfaces such as Cement Plastered Walls, Asbestos or Fibre Cement boards and on other areas where a durable sheen finish is required.

PRODUCT RECOMMENDED USES

- New and previously painted surfaces made from Cement Plaster, Concrete, Brickwork & Gypsum Plaster.
- Asbestos/Fibre Cement Boards.
- Ideal for interior walls – lounge, dining room, bedrooms, study, playroom & passages etc.

PRODUCT BENEFITS

- Pure acrylic paint
- Fully washable
- Soft touch finish
- Stain & dirt resistant
- Apply with Brush or Roller
- 10 Year Guarantee

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of Medal Plaster Primer, followed by two coats of Medal Premium Velvet Silk.

Asbestos/Fibre Cement: Apply one coat of Medal Plaster Primer, followed by two coats of Medal Premium Velvet Silk.

Iron & Steel: Apply one coat of Medal Dual Steel Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Premium Velvet Silk.

Timber/Wood: Sand surface to a smooth finish. Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Premium Velvet Silk.

Gypsum Plaster (Rhino life/Rhino glide): Apply one coat of Medal Plasterbond or Plaster Primer, followed by two coats of Medal Premium Velvet Silk.

APPLICATION

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Medal Plasterbond, prior to applying two coats of Medal Premium Velvet Silk. Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one coat of Medal Universal Undercoat, followed by two coats of Medal Premium Velvet Silk.

COLOUR RANGE

Available in white, standard colours and three different tint bases.

SPREADING RATE

This product will cover approximately 8-10 m² / litre, depending on surface porosity.

TECHNICAL DATA

Type
Finish

Pure Acrylic
Sheen

Drying Time @ 25°C	Touch Dry: 30 Min to 1 hrs. Hard Dry: 4 hrs.
Re-coating Time	4 Hours
Viscosity	95-108 Krebs units
Specific Gravity	1.22 kg / litre
Wash ability	> 10.000 scrubs
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt; 20Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C
- Keep out of reach of children
- Wash hands with Water immediately after use
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

QUALITY GUARANTEE

Medal Paints will guarantee this product for a period of ten years subject to the adherence by the purchaser to comply with the "Instructions for Use "appearing on the reverse side of each can. Refer to the back of pack for more details.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

