

Product Data Sheet



Premium Non-Drip Enamel

No	MP04
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Premium Non-Drip Enamel is a hardwearing semi-gloss polyurethane-based "non-drip" paint, which is suitable for decorating and protecting all interior and exterior surfaces. This product is ideal for use on kitchen and bathroom walls, doors, cupboards, trim and many other areas where a durable semi-gloss finish is required.

PRODUCT RECOMMENDED USES

- New and previously painted surfaces made from Cement Plaster, Concrete, Brickwork & Gypsum Plaster.
- Primed metal & wooden surfaces.
- Ideal for kitchens, bathrooms and trim.

PRODUCT BENEFITS

- Non-Drip enamel
- Fully washable
- Water & steam resistant
- Apply with Brush or Mohair Roller
- 10 Year Guarantee

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of Medal Plaster Primer, and two coats of Premium Non-Drip Enamel.

Asbestos/Fibre Cement: Apply one coat of Medal Plaster Primer, and two coats of Premium Non-Drip Enamel.

Iron & Steel: Remove all grease and surface rust before painting. Apply one coat of Medal Dual Steel Primer, and two coats of Premium Non-Drip Enamel.

Timber/Wood: Sand surface to a smooth finish. Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Premium Non-Drip Enamel.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Medal Bonding Liquid, prior to applying two coats of Premium Non-Drip Enamel. Spot prime all bare areas with the correct primer, and build up any uneven areas with Medal Universal Undercoat. Apply two coats of Premium Non-Drip Enamel.

APPLICATION

Do not stir or shake container before use. If stirred accidentally, leave paint to stand for 4 hours to regain its correct consistency again. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (mohair) paint roller, and allow overnight drying time between coats. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use.

COLOUR RANGE

Available in white, standard colours and three different tint bases

SPREADING RATE

This product will cover approximately 8-10 m² / litre, depending on surface porosity.

TECHNICAL DATA

Type	Polyurethane
Finish	Semi-gloss
Drying Time @ 25°C	Touch Dry: 40 Min to 1 hrs. Hard Dry: 16 hrs
Re-coating Time	16 Hours
Viscosity	100-120 Krebs units
Specific Gravity	1.15 kg / litre
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C
- Keep out of reach of children
- Wash hands with Mineral Turpentine immediately after use
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Mineral Turpentine; Stepladder.

QUALITY GUARANTEE

Medal Paints will guarantee this product for a period of ten years subject to the adherence by the purchaser to comply with the "Instructions for Use" appearing on the reverse side of each can. Refer to the back of pack for more details.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

