

Product Data Sheet



Premium Roof Paint

No	MP05
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Premium Roof Paint is a weather-resistant pure acrylic paint with a sheen finish, which has been developed to provide excellent durability and inhibits fungal and mildew growth. This product is suitable for Asbestos Cement Roof Sheets or Tiles, Cement or Clay Roof Tiles and on primed Galvanised Iron Roofs.

PRODUCT RECOMMENDED USES

- Most types of roofs (exc. Slate)
- Concrete window sills.
- Asbestos/Fibre Cement surfaces such as Fascia Boards; Garden Pots; Gutters & Downpipes.
- Primed Metal & Wooden Surfaces.
- Exterior use.

PRODUCT BENEFITS

- Pure acrylic paint
- Excellent UV resistant
- Quick drying - 2 coats in one day
- Apply with Brush or Roller
- 10 Year Guarantee

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Galvanised Steel: Clean and remove all manufacturers pre-treatment (oil/grease), prior to applying one coat of Medal Dual Steel Primer, followed by two coats of Medal Premium Roof Paint.

Iron & Steel: Remove all grease and surface rust before painting. Apply one coat of Medal Dual Steel Primer, followed by two coats of Medal Premium Roof Paint.

Cement Roof @ Nutec Tiles: Apply the first coat thinned with 10% water to aid penetration, followed by two coats of Medal Premium Roof Paint un-thinned.

Asbestos/Fibre Cement: Apply one coat of Medal Plasterbond, followed by two coats of Medal Premium Roof Paint.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Medal Plasterbond prior to applying two coats of Medal Premium Roof Paint applied unthinned. Ensure the surface is correctly prepared before commencing to paint.

Warning: Avoid painting if the roof is too hot or covered with mildew, which means that the recommended times to paint may vary as indicated under Application.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. For best results, apply this product between 08:00-11:00 hrs. and again from 15:00-18:00 hrs. Apply this product with a paintbrush or (furpile / lambswool) paint roller, and allow +/- 4 hours drying time between coats. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in standard colours.

SPREADING RATE

This product will cover approximately 5-7m² /litre, depending on surface porosity. Nutec tiles will cover approx. 4-5 square m per litre.

TECHNICAL DATA

Type	Pure acrylic
Finish	Sheen
Drying Time @ 25°C	Touch Dry: 30 Min to 1 hrs. Hard Dry: 4 hrs.
Re-coating Time	4 Hours
Viscosity	95-108 Krebs units
Specific Gravity	1.26 kg / litre
Wash ability	> 10,000 Scrubs
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C
- Keep out of reach of children
- Wash hands with water immediately after use
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Block Brush; Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Stepladder

QUALITY GUARANTEE

Medal Paints will guarantee this product for a period of ten years subject to the adherence by the purchaser to comply with the "Instructions for Use "appearing on the reverse side of each can. Refer to

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

