

# Product Data Sheet



## Premium One Coat Paint

No	MP06
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

### DESCRIPTION

Medal Premium One Coat Paint is a pure acrylic paint with an ultra-smooth finish, which has been especially formulated to provide complete cover to all interior and exterior surfaces in one single application. This revolutionary product is fully washable with excellent hiding power, and abrasion, dirt and stain resistant properties. It can be applied to numerous surfaces such as Cement Plastered Walls, Asbestos or Fibre Cement boards and on other areas where a durable ultra-smooth finish is required.

### PRODUCT RECOMMENDED USES

- New or previously painted surfaces made from Cement Plaster; Concrete; Brickwork & Gypsum Plaster.
- Ideal for Interior Walls – Lounge; Dining room Bedrooms; Study; Passages & Exterior Walls.

### PRODUCT BENEFITS

- Pure Acrylic Paint
- One Coat Application
- Fully Washable
- Stain & Dirt Resistant
- Apply with Brush or Roller
- 10 Year Guarantee

### SURFACE PREPARATION

**New Surfaces:** Surface/s must be thoroughly clean, dry and in sound condition before painting.

**Concrete/Cement Plaster:** Apply one coats of Medal Plaster Primer, followed by one coat of Medal Premium One Coat Paint.

**Asbestos/Fibre Cement:** Apply one coat of Medal Plaster Primer, followed by one coat of Medal Premium One Coat Paint.

**Iron & Steel:** Apply one coat of Medal Dual Steel Primer, followed by one coat of Medal Universal Undercoat and one coat of Medal Premium One Coat Paint.

**Timber/Wood:** Sand surface to a smooth finish. Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and one coat of Medal Premium One Coat Paint.

**Gypsum Plaster (Rhinolite/Rhinoglide):** Apply one coat of Medal Plaster Primer, followed by one coat of Medal Premium One Coat Paint.

**Previously Painted Surfaces:** Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Medal Bonding Liquid, prior to applying one coat of Medal Premium One Coat Paint. Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one coat of Medal Universal Undercoat, followed by one coat of Medal Premium One Coat Paint.

### APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply a thick, even coat of paint. Do not overspread this product as this could lead to an uneven film build that may require a second coat. Apply this product with a paintbrush or (furpile / lambswool) paint roller, and allow +/- 4 hours drying time between coats. Clean tools (brushes & rollers) with Water immediately after use.

### COLOUR RANGE

Available in white and standard colours.

### SPREADING RATE

This product will cover approximately 5m<sup>2</sup> /litre, depending on surface porosity.

### TECHNICAL DATA

Type	Pure acrylic
Finish	Semi-Sheen
Drying Time @ 25°C	Touch Dry: 30 Min to 1 hrs. Hard Dry: 4 hrs.
Re-coating Time	4 Hours
Viscosity	95-108 Krebs units
Specific Gravity	1.42 kg / litre
Wash ability	> 10.000 Scrubs
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt; 20Lt

### PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C
- Keep out of reach of children
- Wash hands with water immediately after use
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

### TOOL CHECKLIST

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

### QUALITY GUARANTEE

Medal Paints will guarantee this product for a period of ten years subject to the adherence by the purchaser to comply with the "Instructions for Use "appearing on the reverse side of each can. Refer to the back of pack for more details.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

