

# Product Data Sheet



## Medal Contractors Acrylic PVA

|      |       |
|------|-------|
| No   | MP06  |
| Date | 01/17 |

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

### **DESCRIPTION:**

Medal Contractors Acrylic Pva is a medium quality paint, suitable for all interior and exterior surfaces. This product has excellent filling and hiding power properties. It can be applied to a variety of surfaces where a mat finish is required.

### **PRODUCT USES:**

- New and previously painted surfaces made from Cement Plaster, Concrete, and Brickwork & Gypsum Plaster.
- Asbestos/Fibre Cement Fascias & Ceiling Boards.
- Primed Metal & Wooden Surfaces.
- Interior & Exterior Walls.

### **PRODUCT BENEFITS:**

- Quick Drying
- Good Hiding Power
- Interior & Exterior Use
- 5 Year Guarantee

### **SURFACE PREPARATION:**

**New Surfaces:** Surface/s must be thoroughly clean, dry and in sound condition before painting.

**Concrete/Cement Plaster:** Apply one coat of Medal Plaster Primer, followed by two coats of Medal Contractors Acrylic Pva.

**Asbestos/Fibre Cement:** Apply one coat of Medal Plaster Primer, followed by two coats of Medal Contractors Acrylic Pva.

**Iron & Steel:** Apply one coat of Medal Dual Steel Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Contractors Acrylic Pva.

**Timber/Wood:** Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal

Universal Undercoat and two coats of Medal Contractors Acrylic Pva.

### **Previously Painted Surfaces:**

Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Medal Plasterbond, prior to applying two coats of Medal Contractors Acrylic Pva. Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one coat of Medal Universal Undercoat, followed by two coats of Medal Contractors Acrylic Pva.

### **Gypsum Plaster (Rhinolite/Rhinoglide):**

Apply one coat of Medal Plaster Primer, followed by two coats of Medal Contractors Acrylic Pva.

### **APPLICATION:**

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furpile / lambs wool) paint roller, and allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

### **COLOUR RANGE:**

Available in white and standard colours.

### **SPREADING RATE:**

This product will cover approximately 6-8m<sup>2</sup> /litre, depending on surface porosity. Based on SABS test method.

### **TECHNICAL DATA:**

|                    |  |
|--------------------|--|
| Type               | Acrylic Based Pva                      |
| Finish             | Matt                                   |
| Drying Time @ 25°C | Touch Dry: 30 Min.<br>Hard Dry : 4 Hrs |
| Re-coating Time    | 4 Hours                                |
| F.O.G.             | 25-35µ                                 |
| Viscosity          | 108-120 Krebs units                    |
| Specific Gravity   | 1.45 kg / litre                        |
| Wash ability       | +/-700 Scrubs                          |
| Storage            | Dry and Cool area                      |
| Pack Size          | 5Lt; 20Lt                              |

### **PRECAUTIONS:**

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

### **TOOL CHECKLIST:**

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

### **QUALITY GUARANTEE:**

Medal Paints will guarantee this product for a period of five years subject to the adherence by the purchaser to comply with the "Instructions for Use" appearing on the reverse side of each can. Refer to the back of pack for more details.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

