

Product Data Sheet



MEDAL HIGH GLOSS ENAMEL

No	MP20
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Medal High Gloss Enamel is a superior quality paint suitable for decorating and protecting all interior and exterior surfaces. This product has an excellent gloss level, fully washable, and it can be applied to a variety of surfaces where a long-lasting glossy finish is required.

PRODUCT USES:

- New and previously painted surfaces made from Cement Plaster, Concrete, and Brickwork & Gypsum Plaster.
- Primed Metal & Wooden Surfaces.
- Ideal for Steel Door & Window Frames; Kitchen & Bathroom Walls; Gates; Steel Fencing; Skirting Boards and Garden Furniture etc.

PRODUCT BENEFITS:

- Excellent Durability
- Stain & Dirt Resistant
- Good Hiding Power
- Interior & Exterior Use
- 7 Year Guarantee

SURFACE PREPARATION:

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of Medal Plaster Primer, followed by one coat of Medal Universal Undercoat. Apply two coats of Medal High Gloss Enamel.

Galvanized Iron: Clean and remove all oil/grease prior to applying one coat of Medal Dual Steel Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal High Gloss Enamel.

Iron & Steel: Clean and remove all grease and rust. Apply one coat of Medal Solvent Etch

primer, followed by one coat of Medal Universal Undercoat and two coats of Medal High Gloss Enamel.

Timber/Wood: Sand surface to a smooth finish. Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal High Gloss Enamel.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Spot prime all bare areas with the correct primer, followed by one coat of Medal Universal Undercoat and two coats of Medal High Gloss Enamel.

APPLICATION:

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (mohair) paint roller, and allow overnight drying time between coats. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use.

COLOURRANGE

Available in white, standard colours and three different types of tint bases.

SPREADING RATE

This product will cover approximately 8-10m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

Type	Alkyd
Finish	High Gloss
Drying Time @ 25°C	
Touch Dry:	4 hrs.
Hard Dry:	16 Hours
Re-coating Time	16 Hours
F.O.G.	<10µ
Viscosity	75-80 K/U
Specific Gravity	1.10 kg / litre
Storage area	Dry and Cool
Pack Size	500ml; 1Lt; 5Lt; 20Lt

PRECAUTIONS:

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST:

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

QUALITY GUARANTEE:

Medal Paints will guarantee this product for a period of seven years subject to the adherence by the purchaser to comply with the "Instructions for Use" appearing on the reverse side of each can. Refer to the back of pack for more details.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

