

PRODUCT DATA SHEET

**EVERCURE
DAMP STOP**

No EW11

Date 04/11

Evercure waterproofing products are developed and marketed by Medal Paints to meet the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Evercure Damp Stop is an excellent product, which has been specifically developed to seal and protect all interior and exterior surfaces against rising damp. The use of this product will prevent further deterioration of the substrate as well as protecting the subsequent coats of paint applied to the surface. This product has excellent adhesion and alkali-resistant properties, and is suitable for direct application to Plastered Cement, Concrete or Masonry surfaces.

PRODUCT USES

- Internal and External walls made from Cement Plaster; Concrete and Masonry surfaces.
- Walls plastered below the Damp Proof Course.

PRODUCT BENEFITS

- Alkali Resistant
- Excellent Sealing Properties
- Completely Waterproof
- Apply with Paint Roller
- Interior & Exterior Use
- Quality Guaranteed

SURFACE PREPARATION

Previously Painted Surfaces: Thoroughly clean and prepare Surface/s by removing all loose or flaking paint with a scraper, and stripped back to the original surface. If necessary, use a good quality paint remover, sandpaper or a grinder for this purpose. All areas that are soft as a result of severe damp must be scraped clean and re-plastered (if necessary) and cracks filled in with a Medal Crackfiller, prior to using this product. Apply the first coat of Evercure Damp Stop thinned with 25% Mineral Turpentine, followed by one to two coats un-thinned. Three coats are recommended on very damp surfaces. Apply two coats of paint in the appropriate finish.

Typical Damp Problems: A newly laid driveway, a high built-up of garden soil above the damp proof course or a wall plastered below the damp proof course of a home or building. Outdoor: pot plants or water penetration through a wall from a shower or bathroom.

APPLICATION

Stir the contents thoroughly before use. This product can be thinned with Mineral Turpentine. Apply this product with a paintbrush, and allow overnight drying time between coats. Clean tools (paint brushes) with Mineral Turpentine immediately after use. Note: This product can be applied directly to damp surfaces.

COLOUR RANGE

Available in white.

SPREADING RATE

This product will cover approximately 2m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

Type	Acrylic Resin
Finish	Matt
Drying Time @ 25°C	Touch Dry : 4 Hours Hard Dry : 16 Hours
Viscosity:	85 – 95 Krebs Units
Re-coating Time	16 Hours
Storage	Dry and Cool
Pack Size	1Lt; 5Lt

PRECAUTIONS

- Do not apply if rain is imminent or on surfaces with long-term ponding.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Mineral Turpentine immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

For more information, please contact our Customer Service Centre on 08600 Medal (08600-63325) where we will gladly assist you with any queries you may have. This product is proudly manufactured by Medal Paints (Pty) Ltd. (Est. 1978) Cnr Main Reef & Kelvin Roads, Industria, Johannesburg Tel: (011) 661-5700.

04/2011