

<b>MEDAL</b>	<b>No</b>	<b>MPP09</b>											
<b>BONDING LIQUID (SOLVENT-BASED)</b>	<b>Date</b>	<b>04/11</b>											
Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.													
<p><b>DESCRIPTION</b> Medal Bonding Liquid is a solvent-based primer and sealer, which has been specially formulated to provide excellent penetrating properties for adhesion to very porous surfaces. It can also be used to bind Powdery/Chalked Pva or Lime Wash to the original surface.</p> <p><b>PRODUCT USES</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> Suitable for sealing very porous surfaces such as Asbestos/Fibre Cement and Gypsum Plaster.</li> <li><input type="checkbox"/> Binding Powdery/Chalked Pva or Lime Washed surfaces.</li> </ul> <p><b>PRODUCT BENEFITS</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> Primer &amp; Sealer</li> <li><input type="checkbox"/> Excellent Binding Properties</li> <li><input type="checkbox"/> Ideal for Chalked Pva Surfaces</li> <li><input type="checkbox"/> Apply with Brush or Roller</li> <li><input type="checkbox"/> Interior &amp; Exterior Use</li> <li><input type="checkbox"/> Quality Guaranteed</li> </ul> <p><b>SURFACE PREPARATION</b> <b>New Surfaces:</b> Surface/s must be thoroughly clean, dry and in sound condition before commencing work. <b>Asbestos/Fibre Cement:</b> Apply one coat of Medal Bonding Liquid, followed by two topcoats of paint in the desired finish and colour. Allow sufficient drying time between coats. <b>Gypsum Plaster (Rhinolite/Rhinoglide):</b> Apply one coat of Medal Bonding Liquid, followed by two topcoats of paint in the desired finish and colour</p> <p><b>Previously Painted Surfaces:</b> Surface/s in poor condition such as Powdery/Chalked Pva or Lime-Wash. Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Apply one coat of Medal Bonding Liquid, followed by one coat of Medal Universal Undercoat (if necessary) and two topcoats of paint in the desired finish.</p>	<p><b>APPLICATION</b> Stir the contents thoroughly before use This product should be applied without thinning. If thinning is required use Mineral Turpentine. Apply this product with a paintbrush or (mohair) paint roller, and allow overnight drying time before applying the final coat/s of paint. Clean tools (brushes &amp; rollers) with Mineral Turpentine immediately after use.</p> <p><b>COLOUR RANGE</b> Clear finish.</p> <p><b>SPREADING RATE</b> This product will cover approximately 10-15m<sup>2</sup> /litre, depending on surface porosity. Based on SABS test method.</p> <p><b>TECHNICAL DATA</b></p> <table> <tr> <td>Type</td> <td>Solvent-Based</td> </tr> <tr> <td>Finish</td> <td>Clear</td> </tr> <tr> <td>Drying Time @ 25°C</td> <td>Touch Dry: 40 Minutes Hard Dry : 16 Hours</td> </tr> <tr> <td>Viscosity</td> <td>15 - 25 Sec FC4 Cup @ 25°C</td> </tr> <tr> <td>Storage</td> <td>Dry and Cool area</td> </tr> <tr> <td>Pack Size</td> <td>1Lt; 5Lt</td> </tr> </table> <p><b>PRECAUTIONS</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> Do not apply if rain is imminent</li> <li><input type="checkbox"/> Apply at an ambient temperature lower than 35°C.</li> <li><input type="checkbox"/> Keep out of reach of children.</li> <li><input type="checkbox"/> Wash hands with Mineral Turpentine immediately after use.</li> <li><input type="checkbox"/> Skin or Eye contact: clean with fresh water and consult a physician if necessary.</li> </ul> <p><b>TOOL CHECKLIST</b> Paintbrush &amp; Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Mineral Turpentine; Crackfiller; Paint Scraper; Stepladder.</p> <p><b>QUALITY GUARANTEE</b> This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.</p>	Type	Solvent-Based	Finish	Clear	Drying Time @ 25°C	Touch Dry: 40 Minutes Hard Dry : 16 Hours	Viscosity	15 - 25 Sec FC4 Cup @ 25°C	Storage	Dry and Cool area	Pack Size	1Lt; 5Lt
Type	Solvent-Based												
Finish	Clear												
Drying Time @ 25°C	Touch Dry: 40 Minutes Hard Dry : 16 Hours												
Viscosity	15 - 25 Sec FC4 Cup @ 25°C												
Storage	Dry and Cool area												
Pack Size	1Lt; 5Lt												

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

For more information, please contact our Customer Service Centre on 08600 Medal (08600-63325) where we will gladly assist you with any queries you may have. This product is proudly manufactured by Medal Paints (Pty) Ltd. (Est. 1978) Cnr Main Reef & Kelvin Roads, Industria, Johannesburg Tel: (011) 661-5700.

04/2011

## PRODUCT DATA SHEET

<b>MEDAL</b>	<b>No</b>	<b>MPP10</b>
<b>RED OXIDE PRIMER (WATER-BASED)</b>	<b>Date</b>	<b>04/11</b>