

Product Data Sheet



MEDAL FIELD MARKING PAINT

No	MP07
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Medal Field Line Marking Pva is a medium quality paint, suitable for all exterior surfaces. This product has excellent filling, water resistant and hiding power properties.

PRODUCT RECOMMENDED USES:

- Field (grass)

PRODUCT BENEFITS:

- Quick Drying
- Good Hiding Power
- Exterior Use
- Quality Guaranteed

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Field (grass)

Apply 2 coats of Medal Field Line Marking Pva Paint directly to the field.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Apply two coats of Field Line Marking Paint.

APPLICATION - SPRAY MACHINE:

Stir the contents thoroughly before use. This product **MUST** be applied **WITHOUT** thinning. Apply product and allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools with water immediately after use.

COLOUR RANGE

Available in white.

SPREADING RATE

This product will cover approximately 4-6 m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic Based Pva
Finish	Matt
Drying Time @ 25°C	
Touch Dry:	30 Min to 1 Hour
Hard Dry:	4 Hrs
Re-coating Time	4 Hours
Viscosity	55 - 60 Krebs Units
Specific Gravity	1.04 kg / litre
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS:

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST:

Paintbrush & Paint Roller Tray set or Spraygun and compressor; Plastic Drop Sheet; Mutton Cloth; Masking Tape; Paint Scraper.

QUALITY GUARANTEE:

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

