

Product Data Sheet



Premium Textured Coat

No	MP02
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Premium Textured Coat is a flexible exterior wall coating, which is recommended for use on exterior concrete and cement-plastered surfaces. This product contains Mica for stretch and Granite for strength. It covers all hairline cracks, and it has excellent alkali and water-resistant properties to withstand the harshest climatic conditions. Also suitable on other areas where a fine durable mat textured finish is required.

PRODUCT RECOMMENDED USES

- New and previously painted surfaces made from Cement Plaster, Concrete, Brickwork & Gypsum Plaster.
- Asbestos/Fibre Cement Boards.
- Primed Metal & Wooden Surfaces
- Ideal for Exterior Walls.

PRODUCT BENEFITS

- Acrylic paint
- Excellent elasticity
- Hides hairline cracks
- Excellent UV resistance
- Apply with Brush or Roller
- 10 Year Guarantee

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of Medal Plaster Primer followed by two coats of Medal Premium Textured Coat

Asbestos/Fibre Cement: Apply one coat of Medal Plaster Primer followed by two coats of Medal Premium Textured Coat

Gypsum Plaster (Rhinolite): Apply one coat

of Medal Plaster Primer, followed by two coats of Medal Premium Textured Coat.

Iron & Steel: Apply one coat of Medal Dual Steel Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Premium Textured Coat.

Timber/Wood: Sand surface to a smooth finish. Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Premium Textured Coat.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Lightly sand and apply two coats of Medal Premium Textured Coat.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furpile / lambswool / foam) paint roller, and allow +/- 4 hours drying time between coats. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in white, standard colours and three different tint bases

SPREADING RATE

This product will cover approximately 5-7 m² / litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic Based
Pva Finish	Matt
Drying Time @ 25°C	Touch Dry: 30 Min to 1 hrs. Hard Dry: 4 hrs. 4 Hours
Re-coating Time	4 Hours
Viscosity	125-136 Krebs units
Specific Gravity	1.38 kg / litre
Wash ability	> 10,000 scrubs
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C
- Keep out of reach of children
- Wash hands with Water immediately after use
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

QUALITY GUARANTEE

Medal Paints will guarantee this product for a period of ten years subject to the adherence by the purchaser to comply with the "Instructions for Use" appearing on the reverse side of each can. Refer to the back of pack for more details.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

