

Product Data Sheet



PROFESSIONAL TRADE WATERBASED PLASTER PRIMER

| | |
|------|-------|
| No | MPT2 |
| Date | 01/17 |

Medal Professional Trade products are manufactured to the quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Professional Trade Water-based Plaster Primer is a medium quality paint, suitable for all interior and exterior surfaces. This product has excellent alkali, water resistant and hiding power properties.

PRODUCT RECOMMENDED USES:

- New & previously painted surfaces made from Cement Plaster, Concrete, Brickwork
- Asbestos/Fibre Cement Fascias & Ceiling Boards.
- Interior & Exterior Walls.

PRODUCT BENEFITS

- Quick Drying
- Good Hiding Power
- Apply with Brush or Lamb's wool Roller
- Interior & Exterior Use
- Quality Guaranteed

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of Professional Trade Water-based Plaster Primer followed by two topcoats of paint in the desired finish and colour.

Asbestos/Fibre Cement: Apply one coat of Professional Trade Water-based Plaster Primer followed by two topcoats of paint in the desired finish and colour.

*** Not recommended for Gypsum Plaster (Rhinolite):**

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Lightly sand and apply one coats of Professional Trade Water-based Plaster Primer followed by two topcoats of paint in the desired finish and colour.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. Apply this product with a paintbrush or (furpile / lambswool) paint roller, and allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in white

SPREADING RATE

This product will cover approximately 4-6 m² /litre, depending on surface porosity.

TECHNICAL DATA

| | |
|--------------------|-----------------------------|
| Type | Acrylic Alkali based |
| Primer | |
| Finish | Matt |
| Drying Time @ 25°C | Touch Dry: 30 Min to 1 Hour |
| | Hard Dry : 4 |
| Hours | |
| Re-coating Time | 4 Hours |
| Viscosity | 108-120 Krebs units |
| Specific Gravity | 1.45 kg / litre |

| | |
|------------------|----------------------|
| Water Resistance | >6 hours – No damage |
| Storage | Dry and Cool area |
| Pack Size | 5 & 20L |

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

QUALITY GUARANTEE:

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the consumer.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

