

PRODUCT DATA SHEET

MEDAL GLAZING PUTTY

No	MPA10
Date	04/11

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Glazing Putty is a general-purpose product suitable for glazing steel and wooden window frames, which can be painted once it has had sufficient time to dry.

PRODUCT USES

- ☐ Suitable for Steel and Wooden Window frames.

PRODUCT BENEFITS

- ☐ General Purpose Putty
- ☐ Good Sealing Properties
- ☐ Apply with Putty Knife
- ☐ Interior & Exterior Use
- ☐ Quality Guaranteed

SURFACE PREPARATION

Thoroughly clean and prepare surface by removing all aged putty dirt and flaking paint before commencing work.

New & Previously Painted Surfaces: Painted surfaces in poor condition may have to be primed again prior to glazing.

Soften the putty by kneading by hand, and embed into the window frame. Place the glass onto the puttied area, and press to the correct depth by applying hand pressure. Allow the putty to set for a while before attempting to remove any access from the glazed area. Smooth off to an even finish using a putty knife.

Once the putty has completely dried, it may be painted with one coat of Medal Universal Undercoat and two coats of Medal High Gloss Enamel. The drying process could take approximately 6 weeks, depending on weather conditions.

Precautions: This product must be kneaded before use. It is not suitable for sealing Tanks or Aquariums. Do not add engine oil or paraffin to soften the putty – use Linseed Oil or Mineral Turpentine.

APPLICATION

Remove putty from pack, and knead by for a while until it has regained its normal consistency. Apply this product with a putty knife, and allow this product to set for at least 48 hours before painting. Clean tools (putty knife or paint scraper) with Mineral Turpentine immediately after use.

COLOUR RANGE

Not applicable.

SPREADING RATE

Not applicable.

TECHNICAL DATA

Type	Linseed Oil
Drying Time @ 25°C	Touch Dry: 36-48 Hours
	Hard Dry : 6 Weeks
Storage	Dry and Cool area
Pack Size	500gr; 1kg; 2kg; 5kg; 20kg; 40kg

PRECAUTIONS

- ☐ Do not apply if rain is imminent
- ☐ Apply at an ambient temperature of 5 to 35°C.
- ☐ Keep out of reach of children.
- ☐ Wash hands Mineral Turpentine immediately after use.
- ☐ Skin or Eye contact: clean with fresh water and consult a physician if necessary

TOOL CHECKLIST

Paintbrush; Plastic Drop Sheet; Paint Scraper or Putty Knife; Sandpaper; Masking Tape; Mineral Turpentine; Stepladder.

QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the “Instructions for Use” appearing on the reverse side of each can have been correctly followed by the customer.