

Product Data Sheet



Medal EGGSHELL ENAMEL

No	MP21
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Medal Eggshell Enamel is a high quality paint suitable for the protection and decoration of all interior surfaces where a durable eggshell finish is required. This product is used as a finish coat to a variety of surfaces where a long-lasting semi-gloss finish is required.

PRODUCT USES:

- New and previously painted surfaces made from Cement Plaster, Concrete, and Brickwork & Gypsum Plaster.
- Primed Metal & Wooden Surfaces.
- Ideal for Kitchen and Bathroom Walls.

PRODUCT BENEFITS:

- Good Durability
- Fully Washable
- Excellent Hiding Power
- Interior Use
- 7 Year Guarantee

SURFACE PREPARATION:

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of Medal Plaster Primer, followed by one coat of Medal Universal Undercoat. Apply two coats of Medal Eggshell Enamel.

Galvanized Iron: Clean and remove all oil/grease prior to applying one coat of Medal Dual Steel Primer followed by one coat of Medal Universal Undercoat and two coats of Medal Eggshell Enamel.

Iron & Steel: Clean and remove all grease and rust. Apply one coat of Medal Solvent Etch Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Eggshell Enamel.

Timber/Wood: Sand surface to a smooth finish. Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Eggshell Enamel.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Spot prime all bare areas with the correct primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Eggshell Enamel.

APPLICATION:

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (mohair) paint roller, and allow overnight drying time between coats. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use.

COLOUR RANGE:

Available in white and three different types of tint bases.

SPREADING RATE:

This product will cover approximately 8-10m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

Type	Alkyd
Finish	Semi-Gloss
Drying Time @ 25°C	Touch Dry: 4 Hrs Hard Dry: 16 Hrs
Re-coating Time	16 Hours
F.O.G.	15 - 20µ
Viscosity	75 - 80 Krebs unit
Specific Gravity	1.20 kg / litre
Storage area	Dry and Cool
Pack Size	1Lt; 5Lt; 20Lt

PRECAUTIONS:

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST:

Paintbrush & Paint Roller Trayset;
Plastic Drop Sheet; Mutton Cloth;
Sandpaper; Masking Tape; Crack filler;
Paint Scraper; Stepladder.

QUALITY GUARANTEE:

Medal Paints will guarantee this product for a period of seven years subject to the adherence by the purchaser to comply with the "Instructions for Use" appearing on the reverse side of each can. Refer to the back of pack for more details.

