

Product Data Sheet



Medal CEILING PAINT

No	MP07
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Medal Ceiling Paint is a superior quality Acrylic Pva, which has been specifically designed for interior and exterior ceilings. This product has excellent hiding power properties. It can be applied to ceilings made from different surfaces where a durable smooth mat finish is required

PRODUCT USES

- Suitable for Internal and External Ceilings made from Cement Plaster, Concrete & Gypsum Plaster.

PRODUCT BENEFITS:

- Quick Drying
- Good Hiding Properties
- Smooth Matt Finish
- Interior & Exterior Use
- 7 Year Guarantee

SURFACE PREPARATION:

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Asbestos/Fibre Cement: Apply one coat of Medal Plaster Primer, followed by two coats of Medal Ceiling Paint.

Cement Plaster: Apply one coat of Medal Plaster Primer, followed by two coats of Medal Ceiling Paint. Alternatively, apply one thin coat of Medal Ceiling Paint, followed by two coats un-thinned.

Timber/Wood: Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Ceiling Paint.

Gypsum Plaster (Rhinolite/Rhinoglide): Apply one coat of Medal Plaster Primer, followed by two coats of Medal Ceiling Paint.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Apply two coats of Medal Ceiling Paint direct to the surface. Powdery surfaces must be treated with one coat of Medal Plasterbond, prior to applying two coats of Medal Ceiling Paint. Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one coat of Medal Universal Undercoat, followed by two coats of Medal Ceiling Paint.

APPLICATION:

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furpile / lambswool) paint roller, and allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

COLOURRANGE

Available in white.

SPREADING RATE

This product will cover approximately 6-8m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

Type	Acrylic Based
Pva	
Finish	Matt
Drying Time @ 25°C	Touch Dry: 30 Min.
	Hard Dry : 4 Hrs.
Re-coating Time	4 Hours
F.O.G.	25-35µ
Viscosity	108-120 Krebs unit
Specific Gravity	1.45 kg / litre
Wash ability	+/-700 Scrubs
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS:

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST:

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

QUALITY GUARANTEE:

Medal Paints will guarantee this product for a period of seven years subject to the adherence by the purchaser to comply with the "Instructions for Use" appearing on the reverse side of each can. Refer to the back of pack for more

