

Product Data Sheet



MEDAL WIPE – ON WOOD STAIN

No	MP42
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Medal Wipe-On Wood Stain is a quick drying solvent-based wood stain, which will beautify and enhance the natural grain of wood. Once the timber has been stained, it must be over-coated with a clear varnish to provide long term protection against the elements. This product is suitable for “interior and exterior” wooden surfaces.

PRODUCT USES:

- Suitable for wooden surfaces made from Pine or Meranti.
- Wooden Fascias & Knotty Pine Paneling.
- Knotty Pine Walls & Ceilings.
- Cupboard and Furniture made from wood.

PRODUCT BENEFITS:

- Enhances Natural Grain of Wood
- Long-lasting Finish
- Quick-drying Properties
- Apply with Mutton Cloth
- Interior & Exterior Use
- Quality Guaranteed

SURFACE PREPARATION:

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before staining. Sand surface to a smooth finish (in direction of grain), and remove dust with a clean cloth. Wear household rubber gloves. Apply one coat of Medal Wipe-On Wood Stain, followed by two coats of Medal Clear Wood Varnish, and allow overnight drying time between coats.

Previously Varnished or Painted Surfaces:

This product is not suitable for previously varnished or painted surfaces. These surfaces must be stripped back to bare wood, prior to

following the “Instructions for Use” for New Surfaces.

Recommendation:

- Floors to be over coated Medal Polyurethane Floor Varnish.

APPLICATION:

Shake the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all bottles. Apply this product with a mutton cloth, and allow +/- 30 minutes drying time before applying two coats of Medal Clear Wood Varnish. Allow overnight drying time between coats. All tools (brushes/gloves) must be cleaned with Mineral Turpentine immediately after use.

COLOUR RANGE

Available standard colours.

SPREADING RATE

This product will cover approximately 10-15m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

Type	Spirit Stain
Finish	Matt
Drying Time @ 25°C	Touch Dry: 10 Min. Hard Dry: 30 Min.
Over-coating Time	12-16 hours(Varnish)
Viscosity	10 - 15 Sec FC4
Cup @ 25°C	
Specific Gravity	0.80 kg / lt
Storage	Dry and Cool area
Pack Size	500ml

PRECAUTIONS:

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with hand cleaner and rinse with clean water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST:

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Rubber Gloves.

QUALITY GUARANTEE:

This product is quality guaranteed to last under normal conditions, provided that the “Instructions for Use” appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

