

# Product Data Sheet



## PROFESSIONAL TRADE BONDING LIQUID (SOLVENT)

No	MPT6
Date	01/17

Medal Professional Trade products are manufactured to the quality and performance standards to ensure complete customer satisfaction.

### DESCRIPTION

Professional Trade Bonding Liquid is a solvent-based primer and sealer, which has been specially formulated to provide excellent penetrating properties for adhesion to very porous surfaces. It can also be used to bind Powdery/Chalked Pva or Lime Wash to the original surface.

### PRODUCT USES

- Suitable for sealing very porous surfaces such as Asbestos/Fibre Cement and Gypsum Plaster.
- Binding Powdery/Chalked Pva or Lime Washed surfaces.

### PRODUCT BENEFITS

- Primer & Sealer
- Excellent Binding Properties
- Ideal for Chalked Pva Surfaces
- Apply with Brush or Roller
- Interior & Exterior Use
- Quality Guaranteed

### SURFACE PREPARATION

**New Surfaces:** Surface/s must be thoroughly clean, dry and in sound condition before commencing work.

**Asbestos/Fibre Cement:** Apply one coat of Professional Trade Bonding Liquid, followed by two topcoats of paint in the desired finish and colour.

Allow sufficient drying time between coats.

### **Gypsum Plaster (Rhinolite/Rhinoglide):**

Apply one coat of Professional Trade Bonding Liquid, followed by two topcoats of paint in the desired finish and colour.

**Asbestos/Fibre Cement:** Apply one coat of Professional Trade Bonding Liquid, followed

**Previously Painted Surfaces:** Surface/s in poor condition such as Powdery/Chalked Pva or Lime-Wash. Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Apply one coat of Professional Trade Bonding Liquid, followed by one coat of Professional Trade Universal Undercoat (if necessary) and two topcoats of paint in the desired finish.

### APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. Apply this product with a paintbrush or (mohair) paint roller, and allow overnight drying time before applying the final coat/s of paint. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use.

### COLOUR RANGE

Clear finish

### SPREADING RATE

This product will cover approximately 10-12m<sup>2</sup> /litre, depending on surface porosity.

### TECHNICAL DATA

Type	Solvent-Based
Finish	Clear
Drying Time @ 25°C	Touch Dry: 40 Minutes
	Hard Dry : 16 Hours
Viscosity	15 - 25 Sec FC4
Cup @ 25°C	
Storage	Dry and Cool area
Pack Size	1 & 5L

### PRECAUTIONS

- Do not apply if rain is imminent
- Apply at an ambient temperature lower than 35°C.
- Keep out of reach of children.
- Wash hands with Mineral Turpentine immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

### TOOL CHECKLIST

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Mineral Turpentine; Crack filler; Paint Scraper; Stepladder.

### QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

