

## PRODUCT DATA SHEET

### EVERPRIME BONDING LIQUID

No	EW05
Date	04/11

Everprime Bonding Liquid products are developed and marketed by Medal Paints to meet the highest quality and performance standards to ensure complete customer satisfaction.

#### **DESCRIPTION**

Everprime Bonding Liquid is based on a high quality micro emulsion system, which has been especially formulated to provide excellent penetrating properties for adhesion to porous surfaces. Essentially, this product is used as a bonding agent for waterproofing and paints on raw masonry surfaces, which includes Cement Roof Tiles or Cement-Plastered Walls.

#### **PRODUCT USES**

- ☐ A primer used for new Concrete, Plaster and Asbestos surfaces prior to Painting or Waterproofing.
- ☐ This product is suitable for Roofs and Walls.

#### **PRODUCT BENEFITS**

- ☐ Quick Drying (Water-Based)
- ☐ Excellent Adhesion Properties
- ☐ A Sound Surface for Top Coats
- ☐ Apply with a Brush or Roller
- ☐ Quality Guaranteed

#### **SURFACE PREPARATION**

**New Surfaces:** Surface/s must be thoroughly clean, dry and in sound condition before commencing work.

**Cement Roof Tiles:** Apply one coat of Everprime Bonding Liquid, followed by two coats of Waterproofing or Roof Paint in the desired finish. Allow sufficient drying time between coats.

**Cement Plastered Walls:** Apply one coat of Everprime Bonding Liquid, followed by two coats of Waterproofing or Paint for walls in the desired finish. Allow sufficient drying time between coats.

**Note:** This product is not suitable for Powdery/Chalked Pva, Lime Washed and Gypsum Plastered surfaces. Use Medal Bonding Primer, a solvent-based material instead.

#### **APPLICATION**

Stir the contents thoroughly before use. This product should be applied without thinning. Apply this product with a paintbrush or (mohair) paint roller, and allow +/- 4 hours drying time between coats. Clean tools (paintbrushes/ paint rollers) with Water immediately after use.

#### **COLOUR RANGE**

Milky white that dries to a clear finish.

#### **SPREADING RATE**

This product will cover approximately 9-10m<sup>2</sup> /litre, depending on surface porosity. Based on SABS test method.

#### **TECHNICAL DATA**

Type	Acrylic
Finish	Clear
Drying Time @ 25°C	Touch Dry: 1 Hour Hard Dry : 4 Hours
Viscosity	20 -30 F4 Cup @ 25°C
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt; 20Lt

#### **PRECAUTIONS**

- ☐ Do not apply if rain is imminent.
- ☐ Apply at an ambient temperature of 5 to 35°C.
- ☐ Keep out of reach of children.
- ☐ Wash hands with Water immediately after use.
- ☐ Skin or Eye contact: clean with fresh water and consult a physician if necessary.

#### **GUARANTEE**

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.