

PRODUCT DATA SHEET

MELODY PVA

No	MPL02
Date	04/11

DESCRIPTION

Melody Pva is an economical paint suitable for interior surfaces. This product can be used as a low-cost undercoat for new cement-plastered surfaces to be painted with a better quality Medal Acrylic Pva.

PRODUCT USES

- ☐ Cement Plastered or Brown Mud Walls.
- ☐ Suitable for Garage and Storeroom Walls.
- ☐ Low-Cost Housing.

PRODUCT BENEFITS

- ☐ Smooth Matt Finish
- ☐ Easy to Apply
- ☐ Apply with Brush or Roller
- ☐ Interior Use

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Cement Plaster: Apply one coat of Melody Pva as a first coat, followed by two coats of a better quality Acrylic Pva. For low-cost applications, apply two coats of Melody Pva direct to the surface.

Asbestos/Fibre Cement: Apply one coat of Medal Plasterbond, followed by two coats of Melody Pva.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Apply two coats of Melody Pva direct to the surface. Powdery surfaces must be treated with one coat of Medal Plasterbond, prior to applying two coats of Melody Pva. Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one coat of Medal Universal Undercoat, followed by two coats of Melody Pva.

Warning: This product is specifically made for low-cost applications, and should not be used as a finish coat for normal domestic or commercial use. A better quality Medal Acrylic Pva is highly recommended to provide long-term durability and complete protection against the weathering elements.

Note: This product should be applied un-thinned, as adding water will affect the overall performance of this paint.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (Furpile / Lambswool) paint roller, and allow 50 Minutes drying time between coats. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in white and standard colours.

SPREADING RATE

This product will cover approximately 2-4m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

Type	Acrylic Based Pva
Finish	Matt
Drying Time @ 25°C	Touch Dry: 15 Minutes Hard Dry : 45-50 Minutes
Re-coating Time	50 Minutes
F.O.G.	30-40 µ
Viscosity	85 -100 Krebs Units
Specific Gravity	1.33 kg / litre
Wash ability	5-6 Scrubs
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS

- ☐ Do not apply if rain is imminent.
- ☐ Apply at an ambient temperature of 5 to 35°C.
- ☐ Keep out of reach of children.
- ☐ Wash hands with Water immediately after use.
- ☐ Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paint Brush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Stepladder.