

## PRODUCT DATA SHEET

### MEDAL INDUSTRIAL MONOLAC WOOD PRIMER

No	MI013
Date	04/11

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

#### **DESCRIPTION**

Medal Monolac Wood Primer is a Nitro Cellulose lacquer-based primer used for various industrial applications. This product contains high filling properties combined with excellent binding and adhesion to new and previously painted surfaces. It also provides a smooth finish, and hides all minor imperfections on wooden surfaces.

#### **PRODUCT USES**

- ☐ Suitable for most types of wooden surfaces.
- ☐ Ideal for Kitchen Cupboards & General Woodwork.
- ☐ Motor Cars; Furniture etc

#### **PRODUCT BENEFITS**

- ☐ High Filling Properties
- ☐ Excellent Adhesion
- ☐ Apply with Spray
- ☐ Interior & Exterior Use
- ☐ Quality Guaranteed

#### **SURFACE PREPARATION**

**New Surfaces:** Surface/s must be thoroughly clean, dry and in sound condition before commencing work.

Sand surface (in direction of grain) before applying one coat of Medal Monolac Wood Primer. Sand to a smooth finish. Apply 1-2 coats of paint in the appropriate finish, and allow sufficient drying time between coats.

#### **APPLICATION**

Stir the contents thoroughly before use. This product may be thinned down by up to 20% with Medal Lacquer Thinners for spray application. Apply one coat with a paintbrush or spray and allow two hours drying time before finishing off with two coats of Medal paint in the desired finish. Clean tools (spraying equipment) with Medal Lacquer Thinners immediately after use.

#### **COLOUR RANGE**

Available in white and Grey.

#### **SPREADING RATE**

This product will cover approximately 6-8m<sup>2</sup> /litre, depending on surface porosity. Based on SABS test method.

#### **TECHNICAL DATA**

Type	Nitrocellulose
Finish	Matt
Drying Time @ 25°C	Touch Dry: 5-10 Minutes Hard Dry : 30 Minutes
Re-coating Time	1 Hour
Viscosity	60-70 Sec/F4/25°C
Specific Gravity	1.14 kg / litre
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt; 25Lt

#### **PRECAUTIONS**

- ☐ Do not apply if rain is imminent.
- ☐ Apply at an ambient temperature of 5 to 35°C.
- ☐ Keep out of reach of children.
- ☐ Wash hands with Thinners and Hot Soapy Water immediately after use.
- ☐ Skin or Eye contact: clean with fresh water and consult a physician if necessary.
- ☐ Wear protective clothing.

#### **QUALITY GUARANTEE**

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.