

Product Data Sheet



MEDAL ACRYLOSEAL FOUR IN ONE PVA

No	MP06
Date	09/18

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Medal Acryloseal Four In One Pva is a good quality paint, suitable for all interior and exterior surfaces. This product has excellent filling, water resistant and hiding power properties. It can be applied to a variety of surfaces where a matt finish is required.

PRODUCT RECOMENDED USES:

- New and previously painted surfaces made from Cement Plaster, Concrete, and Brickwork & Prepared Gypsum Plaster.
- Asbestos/Fibre Cement Fascia's & Ceiling Boards.
- Interior & Exterior Walls.

PRODUCT BENEFITS:

- Quick Drying
- Good Hiding Power
- Alkali Resistant
- Interior & Exterior Use
- 7 Year Guarantee
- **Agreement Certified:** provides reassurance of the fitness-for-purpose of a product through an objective assessment by an independent organization.

SURFACE PREPRATION:

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply two coats of Medal Acryloseal Pva,

Asbestos/Fibre Cement: Apply two coat of Medal Acryloseal Pva.

Gypsum Plaster (Rhinolite): Apply one coat of Medal Plaster Primer followed by two coats of Medal Acryloseal Pva.

Previously Painted Surfaces PVA:

Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Lightly sand and apply two coats of Medal Acryloseal Pva.

Previously Painted Surfaces Enamel:

Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Lightly sand and apply one coat of Medal Universal Undercoat and allow to dry for 16 hours then apply two coats of Medal Acryloseal Pva.

Note: Not recommended for clay-based substrates.

APPLICATION:

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furpile / lambswool) paint roller and allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

White, Standard Colours, Pastel and Deep Tintbases.

SPREADING RATE

This product will cover approximately 4-6 m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic Based Pva
Finish	Matt
Drying Time @ 25°C	Touch Dry: 1 Hour
Hard Dry :	4 Hours
Re-coating Time	4 Hours
Viscosity	108-120 Krebs units
Specific Gravity	1.45 kg / litre
Water Resistance	>6 hours – No damage
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS:

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST:

Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

QUALITY GUARANTEE:

Medal Paints will guarantee this product for a period of seven years subject to the adherence by the purchaser to comply with the "Instructions for Use" appearing on the reverse side of each can. Refer to the back of pack for more details.

