

Product Data Sheet



MEDAL CERAMIC TILE and MELAMINE PRIMER

No	MP18
Date	09/18

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Medal Ceramic Tile and Melamine Primer is a high quality pure acrylic based primer, suitable for all interior ceramic wall tiles and melamine surfaces. This product has excellent adhesion, water resistant and hiding power properties.

PRODUCT RECOMMENDED USES

- ☐ New and previously ceramic surfaces
- ☐ Melamine/wood surfaces
- ☐ Interior use only.

PRODUCT BENEFITS

- ☐ Quick Drying
- ☐ Low Odour
- ☐ Excellent Adhesion and Intercoat Adhesion
- ☐ Apply with Brush or Mohair Roller
- ☐ Quality Guaranteed

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting. Treat defect surfaces with Medal Crack filler. It is recommended to replace broken or chipped tiles for better application results. Remove surface contaminants with Medal Liquid Sugar Soap and scotch brite pad. For stubborn stain removal use Medal A1 Degreaser solution (1part degreaser to 10 parts water). Rinse thoroughly with warm water. Allow to dry properly.

Ceramic tile: Apply one coat of Medal Ceramic Tile and Melamine Primer followed by the desired topcoat.

Melamine/ Wood: Apply one coat of Medal Ceramic Tile and Melamine Primer followed by the desired topcoat.

Over-coating time: With decorative water-based topcoat – 4hours. With solvent decorative enamel- 24 hours

Previously Painted Surfaces: Clean surfaces with Medal Liquid Sugar Soap and scotch brite pad. Rinse thoroughly with warm water to remove traces of contaminants. Allow to dry properly. Light sand surfaces for better adhesion and wipe surfaces with damp cloth to remain dust free.

*Not recommended for floor, bath and shower areas or damp conditions and where temperature are below 10 degrees Celsius.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (mohair) paint roller and allow +/- 4 hours drying time. Allow the top coat paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with water immediately after use.

COLOUR RANGE

Available in white

SPREADING RATE

This product will cover approximately 6-8 m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic Based Pva
Finish	Semi - Sheen
Drying Time @ 25°C	Touch Dry: 1 Hour Hard Dry: 4 Hours
Re-coating Time	4 Hours
Viscosity	100--120 Krebs
Units	
Specific Gravity	1.23 kg / litre
Storage	Dry and Cool area
Pack Size	1 Lt

PRECAUTIONS

- ☐ Do not apply if rain is imminent.
- ☐ Apply at an ambient temperature of 10 to 35°C.
- ☐ Keep out of reach of children.
- ☐ Wash hands with Water immediately after use.
- ☐ Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Tray set;
Plastic Drop Sheet; Mutton Cloth;
Sandpaper; Masking Tape; Crack filler;
Paint Scraper; Stepladder.

QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

