

Product Data Sheet



MEDAL STOEP PAINT

No	MP50
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Medal Stoep Paint is a superior quality alkali-resistant enamel based paint, which is primarily used to protect and decorate small concrete floors and window sills. This product is easy to apply and dries to a durable glossy finish.

PRODUCT USES:

- Suitable for Concrete Floors and Window Sills.

PRODUCT BENEFITS:

- Complete Protection
- Durable Glossy Finish
- Fully Washable
- Easy to Clean & Maintain
- Interior & Exterior Use
- Quality Guaranteed

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

New Surfaces: Surfaces must be thoroughly clean, dry and in sound condition and free from polish or wax before painting. Newly laid concrete floors must be allowed to dry for 6 weeks. Smooth floors must be cleaned with hydrochloric acid and rinsed off with water, and allowed to dry before painting. Apply one coat of Medal Stoep Paint thinned with 10% Mineral Turpentine, followed by two coats of Medal Stoep Paint unthinned.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, wax, polish and flaking paint before commencing to paint. Rub down with sandpaper and ensure surface is dry and clean

and in sound condition before applying two coats of Medal Stoep Paint.

Where powdery surfaces are evident, use Medal Bonding Liquid by applying one coat and allow to dry for a period of 16 hours prior to overcoating.

Warning: This product is not suitable for surfaces continually exposed to Oil / Grease or strong Solvents etc.

APPLICATION:

Stir the contents thoroughly before use. This product should be applied without thinning unless to be used on new surfaces. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (mohair) paint roller, and allow 16 hours drying time between coats. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use.

COLOUR RANGE

Available in standard colours.

SPREADING RATE

This product will cover approximately 6-8m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

Type	Alkyd
Finish	High Gloss
Drying Time @ 25°C	Touch Dry: 4 Hrs Hard Dry: 16 Hrs
Re-coating Time	16 Hours
Viscosity	68-72 Krebs units
Specific Gravity	1.10 kg / litre
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt

PRECAUTIONS:

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST:

Paintbrush & Mohair Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

QUALITY GUARANTEE:

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

