

Product Data Sheet



PROFESSIONAL TRADE WATERBASED PLASTER PRIMER

No	MPT2
Date	08/18

Medal Professional Trade products are manufactured to the quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Professional Trade Water-based Plaster Primer is a good quality paint, suitable for all interior and exterior surfaces. This product has excellent alkali, water resistant and hiding power properties.

PRODUCT RECOMMENDED USES

- New & previously painted surfaces made from Cement Plaster, Concrete, Brickwork and Gypsum based surfaces.
- Asbestos/Fibre Cement Fascias & Ceiling Boards.
- Interior & Exterior Walls.

PRODUCT BENEFITS

- Quick Drying
- Good Hiding Power
- Apply with Brush or Lamb's wool Roller
- Interior & Exterior Use
- Quality Guaranteed

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of Professional Trade Water-based Plaster Primer followed by two topcoats of paint in the desired finish and colour.

Asbestos/Fibre Cement: Apply one coat of Professional Trade Water-based Plaster Primer followed by two topcoats of paint in the desired finish and colour.

Gypsum Plaster (Rhinolite): Apply one coat of Professional Trade Water-based

Plaster Primer followed by two topcoats of paint in the desired finish and colour.

Previously Painted Enamel Surfaces:

Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Lightly sand and apply one coat of Medal Universal Undercoat followed by one coat of Professional Trade Water-based Plaster Primer, followed by two topcoats of paint in the desired finish and colour.

Previously Painted Acrylic PVA Surfaces:

Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Lightly sand and clean before applying one coat of Professional Trade Water-based Plaster Primer, followed by two topcoats of paint in the desired finish and colour.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. Apply this product with a paintbrush or (furpile / lambswool) paint roller and allow +/- 4 hours drying time between coats. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in white

SPREADING RATE

This product will cover approximately 4-6 m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic Alkali resistant based Primer
Finish	Matt
Drying Time @ 25°C	Touch Dry: 30 Min to 1 Hour
	Hard Dry: 4 Hours
Re-coating Time	4 Hours
Viscosity	108-120 Krebs units
Specific Gravity	1.45 kg / litre
Water Resistance	>6 hours – No damage
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.
- Overcoat within 72 hours of application.

TOOL CHECKLIST

Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crackfiller; Paint Scraper; Stepladder.

QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

