

PRODUCT DATA SHEET

SAFARI ACRYLIC PVA

No	MPL 01
Date	04/11

DESCRIPTION

Safari Acrylic Pva is a smooth Matt water-based paint suitable for interior & exterior walls and ceilings. This product can be used for direct application to a variety of different surfaces. It can also be used as a low-cost undercoat to be painted with a better quality Medal Acrylic Pva.

PRODUCT USES

- ☐ Cement Plastered Walls.
- ☐ Asbestos/Fibre Cement Ceiling Boards.
- ☐ Suitable for Garage and Storeroom Walls.
- ☐ Low-Cost Housing.

PRODUCT BENEFITS

- ☐ Smooth Matt Finish
- ☐ High Hiding
- ☐ Apply with Brush or Roller
- ☐ Interior & Exterior Use

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Cement Plaster: For low-cost applications, apply two coats of Safari Acrylic Pva direct to the surface. Alternatively apply one coat of Safari Acrylic Pva as a first coat, followed by two coats of a better quality Medal Acrylic Pva.

Asbestos/Fibre Cement: Apply one coat of Medal Plasterbond, followed by two coats of Safari Acrylic Pva.

Iron & Steel: Apply one coat of Medal Dual Steel Primer followed by one coat of Medal Universal Undercoat and two coats of Safari Acrylic Pva.

Timber/Wood: Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Safari Acrylic Pva.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Apply two coats of Safari Acrylic Pva direct to the surface. Powdery surfaces must be treated with one coat of Medal Bonding Liquid prior to applying two coats of Safari Acrylic Pva. Note: Enamel based surfaces to be painted with an Acrylic Pva must be cleaned and prepared correctly. Sand lightly and apply one coat of Medal Universal Undercoat, followed by two coats of Safari Acrylic Pva.

Warning: This product is specifically made for low-cost applications, and should not be used as a finish coat for normal domestic or commercial use. A better quality Medal Acrylic Pva is highly recommended to provide long-term durability and complete protection against the weathering elements.

Note: This product should be applied un-thinned, as adding water will affect the overall performance of this paint.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furpile / lambswool) paint roller, and allow 50 Minutes drying time between coats. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in white and standard colours.

SPREADING RATE

This product will cover approximately 4-6m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

Type	Acrylic Based Pva
Finish	Matt
Drying Time @ 25°C	Touch Dry: 15 Minutes Hard Dry : 45-50 Minutes
Re-coating Time	50 Minutes
F.O.G.	25-30 µ
Viscosity	108-120 Krebs Units
Specific Gravity	1.33 kg / litre
Wash ability	10-20 Scrubs
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS

- ☐ Do not apply if rain is imminent.
- ☐ Apply at an ambient temperature of 5 to 35°C.
- ☐ Keep out of reach of children.
- ☐ Wash hands with Water immediately after use.
- ☐ Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paint Brush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Stepladder.