

PRODUCT DATA SHEET

**SAFARI
HIGH GLOSS ENAMEL**

No	MPL 03
Date	04/11

DESCRIPTION

Safari High Gloss Enamel is a good quality paint suitable for Interior and Exterior surfaces. A durable product that can be applied to a variety of new or previously painted surfaces such as Cement Plaster; Asbestos/Fibre Cement Wood and Steelwork.

PRODUCT USES

- New and previously painted surfaces made from Cement Plaster.
- Primed Metal & Wooden Surfaces.
- Ideal for Steel Door & Window Frames; Interior Walls; Kitchen & Bathroom Walls; Gates; Steel Fencing etc.

PRODUCT BENEFITS

- Glossy Finish
- Fully Washable
- Apply with Brush or Roller
- Interior & Exterior Use

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of Medal Plaster Primer followed by one coat of Medal Universal Undercoat, and two coats Safari High Gloss Enamel.

Galvanised Iron: Remove all oil/grease from surface before painting. Apply one coat of Medal Dual Steel Primer, followed by two coats of Safari High Gloss Enamel.

Iron & Steel: Remove all grease and surface rust before painting. Apply one coat of Solvent Etch Primer followed by one coat of Medal Universal Undercoat, and two coats of Safari High Gloss Enamel.

Timber/Wood: Lightly sand surface to a smooth finish before painting. Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Safari High Gloss Enamel.

Gypsum Plaster: Apply one coat Plaster Primer before applying two coats of Safari High Gloss Enamel.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Spot prime all bare areas with the correct primer, followed by one coat of Medal Universal Undercoat (if applicable) and two coats of Safari High Gloss Enamel.

Warning: This product is specifically made for low-cost applications, and should not be used as a finish coat for normal domestic or commercial use. A better quality enamel paint is highly recommended to provide long-term durability and complete protection against the weathering elements.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. If thinning is required use Mineral Turpentine. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (mohair) paint roller, and allow overnight drying time between coats. Clean tools (brushes & rollers) with Mineral Turpentine immediately after use.

COLOUR RANGE

Available in white and standard colours.

SPREADING RATE

This product will cover approximately 4 - 6m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

Type	Alkyd
Finish	Gloss
Drying Time @ 25°C	Touch Dry: 40 Minutes Hard Dry : 16 Hours
Re-coating Time	16 Hours
F.O.G.	<10 µ
Viscosity	68-72 Krebs units
Specific Gravity	1.10 kg / litre
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature lower than 35°C.
- Keep out of reach of children.
- Wash hands with Mineral Turpentine immediately after use.
- Skin or Eye contact: clean with fresh water immediately and consult a physician if necessary.

TOOL CHECKLIST

Paint Brush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Mineral Turpentine; Stepladder.