


Product Data Sheet



Medal Brick Dressing

No	MP44
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Medal Brick Dressing is an all-weather resistant finish dressing, which is specifically designed to beautify, enhance, and protect interior and exterior brick or stonework. A quick-drying product, which can be used on a variety of surfaces such as face brick, stone and quarry stone surfaces where a durable clear glossy finish is required.

PRODUCT USES:

Suitable for "Interior and Exterior" surfaces made from Brick & Stone.

PRODUCT BENEFITS:

Complete Protection
Enhances the Natural Shades
Easy to Clean & Maintain
Dries to a Clear Glossy Finish
Apply with Brush or Spray
Interior & Exterior

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before varnishing. Apply two coats of Medal Brick Dressing to a clean and prepared surface. Apply un-thinned for best results.

Previously Varnished Surfaces: Thoroughly clean and prepare surface/s to be varnished by removing all dirt, grease, grime, wax, oil and flaking varnish. The entire surface area must be properly cleaned with clean water and allowed to dry for 24 hours before commencing work. Apply two coats of Medal Brick Dressing.

Warning: This product is not suitable for use on Vinyl, Slasto or Ceramic Tiled floors, and must not be used on Damp surfaces.

APPLICATION:

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or spray and allow overnight drying time between coats. For spray application thin this product down with 10% Mineral Turpentine. Clean tools (brushes & equipment) with Mineral Turpentine immediately after use.

COLOURRANGE

Available in clear.

SPREADING RATE

This product will cover approximately 8-10m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

Type	Alkyd
Finish	High Gloss
Drying Time @ 25°C	Touch Dry: 4 Hrs. Hard Dry: 16 Hrs.
Re-coating Time	16 Hours
Viscosity	10-15secs F4 Cup @ 25°C
Specific Gravity	0.90 kg / litre
Storage	Dry and Cool area
Pack Size	1Lt; 5Lt

PRECAUTIONS:

Do not apply if rain is imminent.
Apply at an ambient temperature of 5 to 35°C.
Keep out of reach of children.
Wash hands with Water immediately after use.
Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Trayset;
Plastic Drop Sheet; Mutton Cloth;
Sandpaper; Masking Tape; Crack filler;
Paint Scraper; Stepladder.

QUALITY GUARANTEE:

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

