


Product Data Sheet



MEDAL PAVE COAT

No	MP32
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Medal Pave Coat is a superior quality paint, which was specifically developed to provide an exceptional hardwearing finish for concrete paving bricks. A floor coating that has excellent alkali resistance properties, and provides complete protection against the weathering elements. The paint finish makes it easy to clean and maintain.

PRODUCT USES:

- Suitable for walkways made from Concrete Paving Bricks.

PRODUCT BENEFITS:

- Durable Semi – Sheen Finish
- Excellent Alkali Resistance
- Fully Washable
- Good Hiding Power
- Exterior Use
- 5 Year Guarantee

SURFACE PREPARATION:

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Apply one coat of Medal Plasterbond, followed by two coats of Medal Pave Coat.

Previously Painted Surfaces:

Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Remove grease and grime etc with Medal Sugar Soap mixed with water, and a stiff-bristled brush or broom. Rinse off with clean water and allow to dry. On worn areas, apply one coat of Medal Plasterbond, prior to applying two coats of Medal Pave Coat.

APPLICATION:

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush, block brush or (furpile / lambswool) paint roller, and allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE Available in standard colours.

SPREADING RATE

This product will cover approximately 5-7m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA

Type	Pure Acrylic
Finish	Semi-Sheen
Drying Time @ 25°C	
Touch Dry:	30 Minutes
Hard Dry:	4 Hours
Re-coating Time	4 Hours
Viscosity	95 - 108 K/U
Specific Gravity	1.42 kg / litre
Wash ability	+/- 10 000 scrubs
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS:

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with Water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.
- **Not recommended for Driveways and Garage floors.**

TOOL CHECKLIST:

Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

QUALITY GUARANTEE:

Medal Paints will guarantee this product for a period of five years subject to the adherence by the purchaser to comply with the "Instructions for Use" appearing on the reverse side of each can. Refer to the back of pack for more details

