

Product Data Sheet



MEDAL SUPER ACRYLIC PVA

No	MP01
Date	01/17

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Medal Super Acrylic Pva is a superior quality paint, which has been developed specifically to decorate and protect all interior and exterior surfaces. This product has excellent filling and hiding power properties. It can be applied to a variety of surfaces where a durable mat finish is required.

PRODUCT USES:

New and previously painted surfaces made from Cement Plaster, Concrete, Brickwork & Gypsum Plaster.
Asbestos/Fibre Cement Fascia's & Ceiling Boards.
Primed Metal & Wooden Surfaces.
Ideal for Interior & Exterior Walls.

PRODUCT BENEFITS:

Excellent Durability
Quick Drying
Fully Washable
Good Hiding Power
Interior & Exterior Use
7 Year Guarantee

SURFACE PREPARATION:

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Concrete/Cement Plaster: Apply one coat of Medal Plaster Primer, followed by two coats of Medal Super Acrylic Pva.

Asbestos/Fibre Cement: Apply one coat of Medal Plaster Primer, followed by two coats of Medal Super Acrylic Pva.

Iron & Steel: Apply one coat of Medal Dual Steel Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Super Acrylic Pva.

Timber/Wood: Apply one coat of Medal Pink Wood Primer, followed by one coat of Medal Universal Undercoat and two coats of Medal Super Acrylic Pva.

Gypsum Plaster (Rhinolite/Rhinoglide): Apply one coat of Medal Plaster Primer, followed by two coats of Medal Super Acrylic Pva.

Previously Painted Surfaces:

Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Medal Plasterbond, prior to applying two coats of Medal Super Acrylic Pva. Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one coat of Medal Universal Undercoat, followed by two coats of Medal Super Acrylic Pva.

APPLICATION:

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furpile / lambswool) paint roller, and allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

COLOUR RANGE

Available in white, standard colours and three different types of tint bases.

SPREADING RATE:

This product will cover approximately 6-8m² /litre, depending on surface porosity. Based on SABS test method.

TECHNICAL DATA:

Type	Acrylic Based Pva
Finish	Matt
Drying Time @ 25°C	Touch Dry: 30 Min. Hard Dry : 4 Hrs.
Re-coating Time	4 Hours
Viscosity	108-120 K/U's
Specific Gravity	1.42 kg / litre
Wash ability	+/- 10.000 Scrubs
Storage	Dry and Cool area
Pack Size	1lt; 5Lt; 20Lt

PRECAUTIONS:

Do not apply if rain is imminent.
Apply at an ambient temperature of 5 to 35°C.
Keep out of reach of children.
Wash hands with Water immediately after use.
Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST:

Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

QUALITY GUARANTEE:

Medal Paints will guarantee this product for a period of seven years subject to the adherence by the purchaser to comply with the "Instructions for Use" appearing on the reverse side of each can. Refer to the back of pack for more details.

