

Product Data Sheet



MEDAL ROOF COAT

No	MP30
Date	05/20

Medal products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION:

Medal Roof Coat is a superior quality paint that provides long-life exterior durability combined with excellent alkali resistance. This product will provide complete protection against the harshest climatic conditions. It can be applied to Asbestos/Fibre Cement Tiles or Roof Sheets, Clay or Cement Roof Tiles and pre-primed Galvanized Iron Roofs

PRODUCT RECOMMENDED USES:

- Suitable for most types of Roofing (exc. Slate).
- Concrete Window Sills.
- Primed Metal & Wooden Surfaces.

PRODUCT BENEFITS

- Excellent UV Resistance
- All-Weather Sheen Finish
- Excellent Hiding Power
- Apply with Brush or Roller
- Exterior Use
- 10 Year Guarantee

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Galvanized Iron: Clean and remove all manufacturers pre-treatment (oil/grease), prior to applying one coat of Medal Dual Steel Primer, followed by two coats of Medal Roof Coat.

Iron & Steel: Remove all grease and surface rust before painting. Apply one coat of Medal Dual Steel Primer, followed by two coats of Medal Roof Coat.

Cement Roof / Nutec Tiles: Apply the first coat thinned with 10% water to aid penetration, followed by two coats of Medal Roof Coat un-thinned.

Asbestos/Fibre Cement: Apply one coat of Medal Plasterbond, followed by two coats of Medal Roof Coat.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be sealed with one coat of Medal Plasterbond, prior to applying two coats of Medal Roof Coat.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. For best results, apply this product between 08:00-11:00 hrs and again from 15:00-18:00 hrs. Apply this product with a paintbrush, block brush or (furpile / lambswool) paint roller, and allow +/- 4 hours drying time between coats. Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

COLOURRANGE

Available in standard colours.

SPREADING RATE

This product will cover approximately 5-7m² /litre, depending on surface porosity. Nutec tiles will cover approximately 3-4 m²/litre

Warning: Avoid painting if the roof is too hot or covered with mildew.

TECHNICAL DATA

Type	Acrylic Based PVA
Finish	Sheen
Drying Time @ 25°C	Touch Dry: 30 Min. Hard Dry : 4 Hrs
Re-coating Time	4 Hours
Viscosity	95 - 108 Krebs units
Specific Gravity	1.26 kg / litre
Wash ability	>10.000 Scrubs
Storage	Dry and Cool area
Pack Size	5Lt; 20Lt

PRECAUTIONS

- Do not apply if rain is imminent.
- Apply at an ambient temperature of 5 to 35°C.
- Keep out of reach of children.
- Wash hands with water immediately after use.
- Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Block Brush; Paintbrush & Paint Roller Tray set; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Scrubbing Brushes; Stepladder.

QUALITY GUARANTEE:

Medal Paints will guarantee this product for a period of eight years subject to the adherence by the purchaser to comply with the "Instructions for Use" appearing on the reverse side of each can. Register your guarantee at www.medalpaints.co.za or call our Customer Service Centre on 08600 63325.

