



LOW SHEEN

INTERIOR & EXTERIOR DESCRIPTION

Medal Low Sheen Acrylic PVA is a superior quality paint with a smooth finish, which has been developed to protect and beautify all interior and exterior surfaces. This product is fully washable with excellent dirt and stain resistance. It can be applied to a variety of surfaces where a durable low-sheen finish is required.

No. MP 19
Date: 04/23

MEDAL PRODUCTS ARE MANUFACTURED TO THE HIGHEST QUALITY AND PERFORMANCE STANDARD TO ENSURE COMPLETE CUSTOMER SATISFACTION.

1. PRODUCT USES

New and previously painted surfaces made from Cement Plaster, Concrete, and Brick & Primed Gypsum Plaster.
Asbestos/Fibre Cement Fascias & Ceiling boards.
Primed Metal & Wooden Surfaces.

2. PRODUCT BENEFITS

Stain & Dirt Resistant
Fully Washable
Attractive Smooth Low Sheen
Good Scrub Resistance
Excellent Obliteration
12 Year Guarantee

3. SURFACE PREPARATION

New Surfaces: Surface must be thoroughly clean, dry and in sound condition before painting.

Concrete/ Cement Plaster: Apply one coat of Professional Trade Waterbased Plaster Primer, followed by two coats of Medal Low Sheen Acrylic PVA.

Asbestos/Fibre Cement: Apply one coat of Professional Trade Waterbased Plaster Primer, followed by two coats of Medal Low Sheen Acrylic PVA.

Iron & Steel: Apply one coat of Medal Dual Steel Primer, followed by one coat of Professional Trade Universal Undercoat and two coats of Medal Low Sheen Acrylic PVA.

Timber/Wood: Apply one coat of Medal Pink Wood Primer, followed by one coat of Professional Trade Universal Undercoat and two coats Medal Low Sheen Acrylic PVA.

Gypsum Plaster (Rhinolite/Rhinoglide): Apply one coat of Prof trade Waterbased Plaster Primer, followed by two coats of Medal Low Sheen Acrylic PVA.

Previously Painted Surface: Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Powdery surfaces must be treated with one coat of Professional Trade Plasterbond, prior to applying two coats of Medal Low Sheen Acrylic PVA, Enamel based surfaces must be cleaned and prepared correctly. Sand lightly and apply one coat of Professional Trade Universal Undercoat, followed by two coats of Medal Low Sheen Acrylic PVA.

4. APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furpile/lambswool) paint roller, and allow +/- 4 hours drying time between coats.

Allow paint to cure (hard dry) for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with water immediately after use.

5. COLOUR RANGE

Standard Colour - White

Tint Bases - Clear, Deep and Pastel

6. SPREADING RATE

This product will cover approximately 7-9m² / litre, depending on surface porosity.

7. TECHNICAL DATA

Type:	Acrylic Based PVA
Finish:	Smooth Low Sheen
Drying Time @ 25°C	Touch Dry: 30 Minutes Hard Dry: 4 Hours
Re-coating:	4 Hours
Viscosity:	105 - 115 Krebs units
Specific Gravity	1.22 kg/ Litre
Storage:	Dry and Cool
Pack Size:	1L, 5L & 20L

8. PRECAUTIONS

Do not apply if rain is imminent
Apply at an ambient temperature of 5 to 35°C.
Keep out of reach of children
Wash hands with water immediately after use.
Skin or Eye contact: clean with fresh water and consult a physician if necessary.

9. TOOL CHECKLIST

Paintbrush & Paint Roller Trayset, Plastic Drop Sheet, Mutton Cloth, Sandpaper, Masking Tape, Crack Filler, Paint Scrapper, Stepladder.

10. QUALITY GUARANTEE

Medal Paints will guarantee this product for a period of twelve years subject to the adherence by the purchaser to comply with the "Instructions for Use" appearing on the reverse side of each can. Refer to the back of pack for more details.

The information contained in the data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications deemed necessary.