



## FIRST COAT WATER BASED PLASTER PRIMER

### INTERIOR & EXTERIOR DESCRIPTION

Professional Trade First Coat Water Based Plaster Primer is an economy range paint which provides adhesion to suitable substrates for interior and exterior surfaces. This product has good alkali resistant and hiding power properties.

No. MP 23  
Date: 06/23

MEDAL PRODUCTS ARE MANUFACTURED TO THE HIGHEST QUALITY AND PERFORMANCE STANDARD TO ENSURE COMPLETE CUSTOMER SATISFACTION.

#### 1. PRODUCT USES

New and previously painted surfaces made from Cement Plaster, Concrete and Brickwork.  
Asbestos/Fibre Cement Fascias & Ceiling Boards.  
Not suitable for Gypsum Plaster.

#### 2. PRODUCT BENEFITS

Quick Drying  
Alkali Resistant  
Good Hiding Power

#### 3. SURFACE PREPARATION

**New Surfaces:** Surface/s must be thoroughly clean, dry and in sound condition before commencing work.  
**Cement Plaster/ Brickwork/ Asbestos or Fibre Cement:** Apply one coat of Professional Trade First Coat Water Based Plaster Primer followed by two Medal topcoats in the desired finish.  
**Asbestos/ Fibre Cement:** Apply one coat of Professional Trade First Coat Water Based Plaster Primer followed by two Medal topcoats in the desired finish.  
**Gypsum Plaster (Rhinolite):** Not recommended.  
**Previously Painted Surface:** Thoroughly clean and prepare surface by removing all dirt, grease, grime and flaking paint before painting. Lightly sand and apply one coat of Professional Trade First Coat Water Based Plaster Primer followed by two Medal topcoats in the desired finish.

#### 4. APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For consistency, ensure that the batch numbers are the same on all cans. Apply this product with a paintbrush or furpile/ lambswool paint roller, and allow +/- 4 hours drying time between coats. Ensure the surface is painted within 72 hours once primed. Clean tools ( brushes & rollers) with water immediately after use.

#### 5. COLOUR RANGE

White

#### 6. SPREADING RATE

This product will cover approximately 4-6m<sup>2</sup> / litre, depending on surface porosity.

#### 7. TECHNICAL DATA

Type:	Acrylic Based PVA
Finish:	Matt
Drying Time @ 25°C	Touch Dry: 1 Hour Hard Dry: 4 Hours
Re-coating:	4 Hours
Viscosity:	112-120 Krebs Units
Specific Gravity:	1,35 kg /Litre
Storage:	Dry and Cool
Pack Size:	5L and 20L

#### 8. PRECAUTIONS

Do not apply if rain is imminent

Apply at an ambient temperature of 5 to 35°C.

Keep out of reach of children

Wash hands with water immediately after use.

Skin or Eye contact: clean with fresh water and consult a physician if necessary.

#### 9. TOOL CHECKLIST

Paintbrush , Drop Sheet, Mutton Cloth, Sandpaper, Masking Tape,

Crack Filler, Paint Scraper, Stepladder.

#### 10. QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the "Instruction for Use" appearing on the reverse side of each can have been correctly followed by the customer. Medal Paints does not incur any liability or obligation other than such replacement obligation. In particular, Medal does not incur liability for remedial expenses and/or for any consequential damage or loss.

The information contained in the data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications deemed necessary.