

Product Data Sheet



Steel Cladd All-In-One

No	SC08
Date	07/21

Steel Cladd products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Steel Cladd All in One is a high quality pure acrylic based primer and topcoat in one suitable for all interior and exterior Iron and Steel surfaces. This product has excellent adhesion, water resistance and hiding power properties.

PRODUCT RECOMMENDED USES

- New and previously painted Iron and steel surfaces
- Interior and Exterior Use.

PRODUCT BENEFITS

- Quick Drying
- Low Odour
- Excellent Adhesion and Intercoat Adhesion
- Apply with Brush or Furple Roller
- Quality Guaranteed

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Iron and Steel: Apply two coats of Steel Cladd All in One onto bare substrate.

Not Recommended for use in bath and showers Floors, and kitchen area Damp conditions if temperature below 10 °C

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, rust, grease, and grime before painting. Lightly sand and apply two coats of Steel Cladd All in One.

APPLICATION

Stir the contents thoroughly before use. This product should be applied without thinning. For consistency, ensure that batch numbers are the same on all cans. Apply this product with a paintbrush or (furple) paint roller and allow +/- 4 - 6 hours drying time between coats. Allow paint to cure

for 7 days before attempting to clean the surface. Do not apply when rain is imminent. Clean tools (brushes & rollers) with Water immediately after use.

Please Note: Do not use a spray application

COLOUR RANGE

Available in White, Black, Brown, Charcoal, Grey, Green, Red

SPREADING RATE

This product will cover approximately 6-8 m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic Based Pva
Finish	Semi - Sheen
Drying Time @ 25°C	Touch Dry: 2 Hours Hard Dry : 4 - 6 Hours
Re-coating Time	4 - 6 Hours
Viscosity	100 -120 Krebs Units
Specific Gravity	1.00-1.20 kg / litre
Storage	Dry and Cool area
Pack Size	1Lt, 5Lt and 20Lt

PRECAUTIONS

Do not apply if rain is imminent.

Apply at an ambient temperature of 5 to 35°C.

Keep out of reach of children.

Wash hands with Water immediately after use.

Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush & Paint Roller Trayset; Plastic Drop Sheet; Mutton Cloth; Sandpaper; Masking Tape; Crack filler; Paint Scraper; Stepladder.

QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer.

