

Product Data Sheet



Evercure Damp Stop

No	EC02
Date	01/24

Ever Range products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Evercure Damp Stop is an excellent product, which has been specifically developed to seal and protect all interior and exterior surfaces against rising damp. The use of this product will prevent further deterioration of the substrate as well as protect the subsequent coats of paint applied to the surface. This product has excellent adhesion and alkali-resistant properties, and is suitable for direct application to Plastered Cement, Concrete or Masonry surfaces.

PRODUCT RECOMMENDED USES

- Internal and External walls made from Cement Plaster, Concrete and masonry surfaces.
- Walls plastered below the Damp Proof Course.

PRODUCT BENEFITS

- Alkali Resistant
- Excellent Sealing Properties
- Completely Waterproof
-

SURFACE PREPARATION

New & Previously Painted Surfaces:

Thoroughly clean and prepare surface/s by removing all loose flaking paint with a scraper, and strip back to the original surface. If necessary, use sandpaper for this purpose. All areas that are soft as a result of severe damp must be scraped, cleaned and re-plastered (if necessary) and cracks filled in with Medal Crack Filler, lightly sand to a smooth finish prior to using this product. Apply the first coat of Evercure Damp Stop thinned with 10% Medal Mineral Turpentine, followed by one coat of un-thinned. Two coats is recommended on very damp surfaces. Thereafter apply two coats of a topcoat in the desired finish.

APPLICATION: Stir the contents thoroughly before use. This product can be thinned with Medal Mineral Turpentine. Apply this product with a paintbrush, and allow overnight drying time between coats. Clean tools (paint brushes) with Mineral Turpentine immediately after use. Note: This product can be applied directly to damp surfaces.

SPREADING RATE

This product will cover approximately 4-6 m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Acrylic Resin
Finish	Matt
Drying Time @ 25°C	Touch Dry: 4 Hour Hard Dry: 16 Hours
Re-coating Time	16 Hours
Viscosity	85-95 Krebs Units
Storage	Dry and Cool area
Pack Size	1Lt & 5Lt

PRECAUTIONS

Do not apply if rain is imminent.
Apply at an ambient temperature lower than 35°C.
Keep out of reach of children.
Wash hands with Road Marking Reducer immediately after use and final wash with soap and water.
Skin or Eye contact: clean with fresh water and consult a physician if necessary.
Do not inhale- use in a well ventilated area.
Wear protective clothing and gloves.
Flammable – keep away from heat and use a fire extinguisher in case of a fire.

TOOL CHECKLIST

Paintbrush, Paint Roller Tray set, Plastic Drop Sheet, Mutton Cloth, Sandpaper, Masking Tape, Paint Scraper, and Stepladder

QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer. Medal paints does not incur any liability or obligation other than such replacement obligation. In particular, Medal does not incur any liability for remedial expenses and/or for any consequential damages or loss.

The information contained in this data sheet is provided in good faith and correct to the best of our knowledge, but Medal Paints reserves the right to change these specifications if deemed necessary.

