

Product Data Sheet



Everflex Liquid Rubber Coating

No	EF01
Date	01/24

Ever Range products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

DESCRIPTION

Everflex Liquid Rubber Coating is specially designed for roofs and cold application, where a high degree of water resistance, elongation and elasticity is required. It also provides outstanding tensile properties and unmatched dirt pickup resistance, ensuring roof surface stays clean.

PRODUCT RECOMMENDED USES

- Primed Metal and Galvanized Iron
- Roof Tiles, Facades and Parapets
- Flashings, Roof Bolts, Laps and Joints
- Cold Room

PRODUCT BENEFITS

- Excellent Flexibility, Stretch and Recovery
- Improved Alkali Resistance
- Improved Lifespan of Coated Substrate
- UV Resistant
- Dirt Pickup Resistance

SURFACE PREPARATION

New Surfaces: Surface/s must be thoroughly clean, dry and in sound condition before painting.

Galvanized Steel: Clean and remove all manufacturers pre-treatment (oil/grease), prior to applying one coat of Medal Dual Steel Primer, followed by two coats of Everflex Liquid Rubber Coating.

Iron & Steel: Remove all grease and surface rust before painting. Apply one coat of Medal Dual Steel Primer followed by two coats of Everflex Liquid Rubber Coating.

Asbestos/Fibre Cement/ Tiles: Apply one coat of Medal Plasterbond, followed by two coats of Everflex Liquid Rubber Coating.

Previously Painted Surfaces: Thoroughly clean and prepare surface by removing all dirt, grease, grime, and flaking paint before painting. Powdery surfaces must be treated with one coat of Medal Plasterbond prior to applying two coats of Everflex Liquid Rubber Coating. Ensure the surface is correctly prepared before commencing to paint.

Warning: Avoid painting if the roof is too hot or covered with mildew, as the recommended times to paint may vary as indicated under application.

APPLICATION: Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. For best results, apply this product between 08:00-11:00 hrs and again from 15:00-18:00 hrs. Apply this product

with a paintbrush or (furpile / lambswool) paint roller and allow +/- 4 hours drying time between coats. Clean tools (brushes & rollers) with immediately after use.

COLOUR RANGE

Black, Burgundy, Charcoal, Grey, Green, Red and Terra Cotta

SPREADING RATE

This product will cover approximately 3-4 m² /litre, depending on surface porosity.

TECHNICAL DATA

Type	Pure Acrylic
Finish	Sheen
Drying Time @ 25°C	Touch Dry: 1 Hour Hard Dry: 4 Hours
Re-coating Time	4Hours
Viscosity	100-115 Krebs Units
Specific Gravity	1.24 kg/ litre
Washability	> 10.000 Scrubs
Storage	Dry and Cool area
Pack Size	5Lt & 20Lt

PRECAUTIONS

Do not apply if rain is imminent.

Apply at an ambient temperature lower than 35°C.

Keep out of reach of children.

Wash hands with Road Marking Reducer immediately after use and final wash with soap and water.

Skin or Eye contact: clean with fresh water and consult a physician if necessary.

TOOL CHECKLIST

Paintbrush, Paint Roller Tray set, Plastic Drop Sheet, Mutton Cloth, Sandpaper, Masking Tape, Paint Scraper, and Stepladder

QUALITY GUARANTEE

This product is marketed by Medal Paints under the Everbond Brand name, which is guaranteed for a period of up to twelve years subject to: 1. The affected surfaces/s are maintained every 4 years with one coat of Everflex Liquid Rubber Coating and 2. The "instruction for use" listed under the relevant Data Specification sheets have been correctly followed by the end user.