

# Product Data Sheet



## Everseal Flexible Waterproofing

No	ES01
Date	01/24

Ever Range products are manufactured to the highest quality and performance standards to ensure complete customer satisfaction.

### DESCRIPTION

Everseal Flexible Waterproofing is a high-quality acrylic waterproofing used in conjunction with a membrane, which has been especially to seal and protect all exterior surfaces. A highly flexible product with excellent elongation and UV resistant properties, which can be applied to a variety of surfaces where a "water-tight" system is required.

### PRODUCT RECOMMENDED USES

- Waterproofing Roofs, Walls and Parapet Walls.
- Flashings, Roof Valleys, Overlapping Roof Sheets.
- Roof Screws and Weather Walls
- Ideal for Galvanised Iron and Tiled Roofs.
- Over-Coat with Water-Based Paints.

### PRODUCT BENEFITS

- Non-Toxic (water-based)
- Provides Complete Protection
- Excellent UV Resistance

### SURFACE PREPARATION

**New Surfaces:** Surface/s must be thoroughly clean, dry and in sound condition before commencing to waterproof.

**Roofs, Parapets & Flashing:** Apply one thick based-coat to the surface. Place membrane firmly onto the base-coat, apply another coat while the treated surface area is still wet. Allow sufficient time to dry before applying the final coat of Everseal. Apply two coats of a good quality Roof Paint.

**Cement Plastered Walls:** Apply one thick base-coat to the surface. Place membrane firmly onto the based-coat, and apply another coat while the treated surface area is still wet. Allow sufficient time to dry before applying one to two finish coats of a good quality exterior Acrylic PVA.

**Previously Painted/Waterproofed Surfaces:** Thoroughly clean and prepare surface by removing all dirt, grease, grime, surface rust, old waterproofing and flaking paint. Apply this product as described under New Surfaces. Powdery surfaces must be sealed with one coat of Everprime Bonding Liquid, prior to using this product.

**APPLICATION:** Stir the contents thoroughly before use. This product should be applied without thinning. For colour consistency, ensure that batch numbers are the same on all cans. For best results, apply this product between 08:00-11:00 hrs and again from 15:00-18:00 hrs. Apply this product

with a paintbrush and allow 4 to 8 hours drying time between coats. Clean tools (brushes & rollers) with immediately after use.

**Warning:** Ensure that the membrane is completely saturated with waterproofing liquid, and applied correctly without creating or entrapped air. Do not apply if rain is imminent or on surfaces with long-term ponding.

### COLOUR RANGE

White, Black, Burgundy, Charcoal, Grey, Historical Green, Red and Terra Cotta

### SPREADING RATE

This product will cover approximately 4 m<sup>2</sup> /litre, depending on surface porosity.

### TECHNICAL DATA

<b>Type</b>	Acrylic
<b>Finish</b>	Semi-Sheen
<b>Drying Time @ 25°C</b>	Touch Dry: 30 Min to 1 Hour Hard Dry: 24-48 Hours
<b>Re-coating Time</b>	4-6 Hours
<b>Viscosity Krebs Units</b>	95-108 Kus
<b>Tensile Strength</b>	2.2 Mpa
<b>Flexibility</b>	100%
<b>Storage</b>	Dry and Cool area
<b>Pack Size</b>	1Lt & 5Lt

### PRECAUTIONS

Do not apply if rain is imminent.

Apply at an ambient temperature lower than 35°C.

Keep out of reach of children.

Wash hands with Road Marking Reducer immediately after use and final wash with soap and water.

Skin or Eye contact: clean with fresh water and consult a physician if necessary.

### TOOL CHECKLIST

Paintbrush, Paint Roller Tray set, Plastic Drop Sheet, Mutton Cloth, Sandpaper, Masking Tape, Paint Scraper, and Stepladder

### QUALITY GUARANTEE

This product is quality guaranteed to last under normal conditions, provided that the "Instructions for Use" appearing on the reverse side of each can have been correctly followed by the customer. Medal Paints does not incur any liability or obligation other than such replacement obligation. In particular, Medal does not incur any liability for remedial expenses and/or for any consequential damages or loss.

